




















Accessory - Converter & Booster

					
Model	AA002	AD001	AD001H	AD001HH	CA101
AV I/O	In:1* Mic Out:1* Audio(RCA)	In:1* Video(BNC) Out:1* VGA	In:1* Video(BNC) , Out: 1* BNC,1*VGA	In:1* Video(RCA) , 1* Stereo Audio(RCA) Out: 1* Video(RCA) , 1* Stereo Audio(RCA) 1* VGA,1*HDMI , 1* 3.5mm PhoneJack	In:1* Video(BNC) , Out:1* Video(BNC)
Other I/O	-	-	-	-	-
Tx Range(approx)	3~5m				1000m
Feature	DC12V	Resolution:768*576, DC5V,convert Video to VGA	Res.:640*480,800*600, 1024*768,1280*1024	Res.:800*600,1024*768 1280*1024,1920*1080	Adj.Sharp/Bright,DC12V video gain amplifier

					
Model	CB001VH	CD102A-U	CD102U	CD104U	CD108U
AV I/O	In:1* Video(BNC) , Out:1* Video(BNC)	In:1* Video(BNC) , Out:2* Video(BNC)	In:1* Video(BNC) , Out:2* Video(BNC)	In:1* Video(BNC) , Out:4* Video(BNC)	In:1* Video(BNC) , Out:8* Video(BNC)
Other I/O	-	-	-	-	-
Tx Range(approx)	-	1000m	300m ~ CD ~ 300m	300m ~ CD ~ 300m	300m ~ CD ~ 300m
Feature	Immune interference from video,data,power	1 to 2 Video Distributor, Adj.Sharp/Bright,DC12V	1 to 2 Video Distributor, DC12/AC24V	1 to 4 Video Distributor, DC12/AC24V	1 to 8 Video Distributor, DC12V

					
Model	CD116U	CD816/U	CD816P	EP01	GL001
AV I/O	In:1* Video(BNC) , Out:16* Video(BNC)	In:8* Video(BNC) , Out:16* Video(BNC)	In:8* Video(BNC) , Out:16* Video(BNC)	-	In:1* Video(BNC) , Out:1* Video(BNC)
Other I/O	-	-	-	In:1* RJ45 , Out:1* RJ45 In:1* DC	-
Tx Range(approx)	300m ~ CD ~ 300m	300m ~ CD ~ 300m	300m ~ CD ~ 300m	30~40m	-
Feature	1 to 16 Video Distributor, DC12V	8 to 16 Video Distributor,DC12/AC24V	8 to 16 Video Distributor, DC12/AC24V	POE Transmission	Prevent Video Distortion Eliminate crossTalk,rolling






					
Model	HE01S	HVY01	IP01	IP01H	IP03
AV I/O	In:1* HDMI , Out:1* CAT5e	In:1* HDMI , Out:1* VGA,1*St.Audio	-	-	-
Other I/O	-	Out:1* Component(YPbPr)	In:1* CAT5e Out:1* Video(BNC)	In:1* CAT5e Out:4* Video(BNC)	In:1* CAT5e Out:1* Video(BNC)
Tx Range(approx)	40~60m	-	100~200m	100~200m	1000~1500m
Feature	HDMI to CAT5e extender	HDMI to VGA/YPbPr, St.Audio, DC5V2A	CAT5e/IP to Coaxial converter	CAT5e/IP to 4*Coaxial switch, DC5V1A	CAT5e/IP to Coaxial converter,DC5V2A






					
Model	IP04X				
AV I/O	-				
Other I/O	In:1* CAT5e Out:1* CAT5e				
Tx Range(approx)	120m ~ CD ~ 120m				
Feature	POE Repeater				






* (T) = Terminal






** Design & specification are subject to change without prior notice **

Accessory - Converter & Booster

					
Model	IP05H	PD009	RS001	RS001R	RS004
AV I/O	-	-	-	-	-
Other I/O	In:1*CAT5e Out:4*CAT5e	In:1*DC(T), Out:9*DC(T)	In:1*RS232, Out:1*RS485	In:1*RS485, Out:1*RS485	In:1*RS232, 2*RS485, Out:4*RS485
Tx Range(approx)	80~120m	-	1200m	1200m <-- R --> 1200m	1200m
Feature	5 port POE Gigabit Switch,DC48V1.36A	AC/DC30V(max)Fused DC Distributor	connect <= 32*camera Convert RS232~RS485	DC12V,Data repeater	DC12V,Data distributor Convert RS232~RS485

					
Model	RS016	SP001	SP001P	SP001VPD	SP002
AV I/O	-	In:1*Video(BNC), Out:1*Video(BNC)	-	In:1*Video(BNC), Out:1*Video(BNC)	In:1*Video(F), Out:1*Video(F)
Other I/O	In:1*RS232, 2*RS485, Out:16*RS485	-	In:1*DC(T), Out:1*DC(T)	In:1*RS485+DC Out:1*RS485+DC	-
Tx Range(approx)	1200m	-	-	-	-
Feature	Data Distributor,DC12V	Coaxial Surge Protector	Power Surge Protector	Video,Power,Data Surge Protector	Coaxial Surge Protector






					
Model	SP006	SP006P	SP016C	SP016N	SP016T
AV I/O	-	-	In:16*Video(BNC), Out:16*Video(BNC)	-	-
Other I/O	In:1*RJ45, Out:1*RJ45	In:1*RJ45, Out:1*RJ45	-	In:16*RJ45, Out:16*RJ45	In:16*Video(T), Out:16*Video(T)
Tx Range(approx)	-	-	-	-	-
Feature	Network Surge Protector	POE Surge Protector	Coaxial Surge Protector	POE Surge Protector	UTP Surge Protector






					
Model	SR01	TPA008H-U	TTA111VT	TTA414VR	TTP111VL
AV I/O	-	Out:16*Video(BNC)	In:1*Video(BNC), Out:1*Video(T)	In:4*Video(BNC), Out:4*Video(T)	In:1*Video(BNC), Out:1*Video(T)
Other I/O	In:1*RJ45, Out:1*RJ45	In:8*Video(T)	-	-	-
Tx Range(approx)	120m ~ CD ~ 120m	Color:900m, B/W:1500m	Color:900m, B/W:1500m	Color:900m, B/W:1500m	Color:400m, B/W:600m
Feature	CAT5e / Data signal extender, DC5V1A	DC12V,Gain,Brightness Video Rx Distributor	DC12V,Gain, Video Tx	DC12V,Gain,Brightness Video Rx	Video Transceiver c/w cable




* (T) = Terminal

** Design & specification are subject to change without prior notice **

Accessory - Converter & Booster

Model					
AV I/O	In:1*Video(BNC)	In:1*Video(BNC)	In:1*Video(BNC), Out:1*Video(T)	In:4*Video(BNC) or 3*Video(BNC)+1*RS485	In:1*(T), Out:1*(T)
Other I/O	In:1*DC Out:1*RJ45	In:1*DC,1*RS485 Out:1*RJ45	-	Out:1*RJ45	-
Tx Range(approx)	Color:400m,Bw:600m DC:(C)50m,(Bw)100m	Color:400m, B/W:600m	Color:400m, B/W:600m	Color:400m, B/W:600m	-
Feature	Video+DC Transceiver	Video+DC+Data Transceiver	Video Transceiver	Video+Data Transceiver	Immune interference from video,data,power






Model					
AV I/O	-	In:1*VGA, Out:2*Video (1*VGA,1*BNC)	In:1*VGA	In:1*VGA,1*St.A(jack) Out:4*VGA,1*St.A(jack)	In:1*VGA Out:1*RJ45
Other I/O	In:4*USB, Out:1*RJ45	-	In:1*RS232, Out:1*RJ45	-	-
Tx Range(approx)	50m	-	300m	-	50~70m (1920*1200)
Feature	USB to CAT5e signal extender DC5v1.2A	Resolution:640*480, 800*600,1024*768 VGA~Video Converter	DC12V,Res.:1600*1200 VGA+RS232 Extender	VGA 1 to 4 Distributor, DC5V1A	VGA to CAT5e converter DC12V0.5A






Model					
AV I/O	In:1*VGA Out:1*RJ45	In:1*VGA,1*St.A Out: 1*VGA,HDMI,St.A			(Tx) I/O : 1*Video(BNC) (Rx) I/O : 1*Video(BNC)
Other I/O	-	-			
Tx Range(approx)	60~135m (1280*1024 ~ 640*480)	-			100 ~ 250m
Feature	VGA to CAT5e converter	VGA to HDMI converter w/Stereo Audio, DC5V2A			Eliminate interference, Boost up signal DC12V1A


* (T) = Terminal



** Design & specification are subject to change without prior notice **

Accessory - Converter & Booster

					
Model	AU801	BA07	PC01S	TV06S	VA04
AV I/O	-	In:1* Mic , Out:1* Audio(RCA)	-	In:1* Video(RCA) In:1* St.Audio(RCA)	In:4* Video(BNC) , Out:4* Video(BNC)
Other I/O	In:8* RS485 , Out:1* RS485	-	In:1* RS232 , Out:1* RS485	Out: 1* RF	-
Tx Range(approx)	1200m	-	-	200m	300m
Feature	8* Keyboard Controller inputs, control up to 256* Speeddomes	Mic	RS232 to RS485 converter	DC12V , AV~TV ch. modulator	DC12V/AC24v , Individual Gain Adj. , Video Distributor

					
Model	W101AV	W102T	W102R	W103T	W103R
AV I/O	In:1* Video(BNC) , Out:2* Audio(RCA)	In:1* Video(BNC/ T) In:1* Audio(RCA/ T)	Out:1* Video(BNC/ T) Out:1* Audio(RCA/ T)	In:1* Video(BNC) , Out:1* Video(T)	In:1* Video(T) , Out:1* Video(BNC)
Other I/O	Out:1* RJ45	Out:1* RJ45 In:1* Data(T) ,1* Sensor(T)	In:1* RJ45 Out:1* Data(T) ,1* Sensor(T)	-	-
Tx Range(approx)	Color:400m, B/W:600m	Color:1500m, B/W:2400m	Color:1500m, B/W:2400m	Color:1500m, B/W:2400m	Color:1500m, B/W:2400m
Feature	Built-in video couple, audio impedance match., AV Transceiver	DC12V , AV+Data Tx	DC12V , AV+Data Rx	DC12V , Video Tx	DC12V , Video Rx , Adjustable Gain

					
Model	W116R	W414VP	V-2006	VGA-Ext4	VG-206
AV I/O	In:16* Video(T) , Out:16* Video(BNC)	-	Video:1* In+6*Out or Video:2* In+3*Out	In:1* VGA , Out:4* VGA	In:1* Video(RCA) , 1* Svideo ,1* St.Audio Out:1* USB
Other I/O	-	In:4* RJ45 , Out:1* RJ45	-	-	-
Tx Range(approx)	Color:400m, B/W:600m	Color:400m, B/W:600m	-	65m	-
Feature	DC12V , UTP Rx	UTP+Power Transceiver	AC220V , Video Distributor	VGA Distributor	Convert AV to USB

					
Model	V-300LS	V-MC01	WC-TGP002A	FUM-F1	
AV I/O	In:1* Mic Out:1* Audio(T)	In:1* Mic Out:1* Audio(RCA)		In:1* Video(BNC) , Out:1* Video(BNC)	
Other I/O	-	-		In:1* DC(T) , Out:1* DC(T)	
Tx Range(approx)	4~8m	3~5m		-	
Feature	DC9~12V , Adj.Sensitivity	DC9~12V		Coaxial + DC Surge Protector	

* (T) = Terminal

** Design & specification are subject to change without prior notice **