

ROISCOK - Alarm Sensor



RK-125DT Dual Tech. Motion Detector

- Power : DC 9~16V (25mA at DC12V)
- Coverage : 25m (max)
- White light protection
- Selectable pulse count
- Free swivel bracket for wall & ceiling mount.
- Anti-fluorescent interference signal processing
- High RFI immunity for false alarm prevention 20v/m up to 1 GHz



RK-410PR Motion Detector

- Power : DC 9~16V (25mA at DC12V)
- Coverage : 12m (max)
- White light protection
- Selectable pulse count
- Free swivel bracket for wall & ceiling mount.
- Anti-fluorescent interference signal processing
- High RFI immunity for false alarm prevention 20v/m up to 1 GHz



RK-2000PR Ceiling Motion Detector

- Power : DC 9~16V (15mA at DC12V)
- Coverage : 6.8m x 110° (max)
- Alarm Output : DC24V 50mA (NC)
- Tamper Output : DC24V 500mA (NC)
- Alarm Time : 2 minutes
- Warmup time : 2 minutes
- Operating Temp. : 0 ~ 50°C
- Storage Temp. : -20°C ~ 60°C
- Size : 110(o) x 26(h) mm



SS - 168A Standalone Smoke Detector w/Buzzer

- Power : DC 12V Battery
- Power Consumption : 10~30mA
- Operation Temperature : -5°C ~ 50°C
- Buzzer loudness : 85dB
- Adjustable NO/NC Relay Output



RK-308 Mini Curtain Motion Detector

- Power : DC 9~16V (15mA at DC12V)
- Coverage : 12m (max), 90°
- White light protection
- Selectable pulse count
- Anti-fluorescent interference signal processing
- High RFI immunity for false alarm prevention 20v/m up to 1 GHz
- Dimension: 45(w)*65(h)*36(d) mm

** Design & specification are subject to change without prior notice **