

Wireless Alarm Siren + Motion Detector



MDFM-235 Wireless Motion Sensor

Tx Distance : 30m (open space)
 Coverage : 6*12m, 90°
 Tx Frequency : 433MHz
 Power supply : DC3V
 Power Consumption : Static ~ ≤ 8mA
 Tx ~ ≤ 500mA
 Anti White Light : > 9000 Lux
 Operation Temperature : -10°C ~ 50°C
 Storage Temperature : -20°C ~ 60°C
 Dimension : 64(w) x 95(h) x 49(d) mm



MDT-15 Motion Sensor

Tx Distance : 30m (open space)
 Coverage : 12*12m, 90°
 Alarm Output : N.C. (≤100mA, DC30V)
 Tx Frequency : 433MHz
 Anti White Light : > 9000 Lux
 Anti Freq.Interruption: >20V/m
 (20MHz~1000MHz)

Power supply : DC9~16V
 Power Consumption : 20mA(DC12V)
 Operation Temperature : -10°C ~ 50°C
 Storage Temperature : -20°C ~ 60°C
 Dimension : 69(w) x 137(h) x 55(d) mm



MDT-7300 Motion Sensor


Tx Distance : 30m (open space)
 Coverage : 11*11m, 90°
 Alarm Output : N.C. (>100mA, DC30V)
 Tx Frequency : 433MHz
 Anti White Light : > 9000 Lux
 Anti Freq.Interruption: >20V/m
 (20MHz~1000MHz)

Power supply : DC9~16V
 Power Consumption : 20mA(DC12V)
 Operation Temperature : -10°C ~ 50°C
 Storage Temperature : -20°C ~ 60°C
 Dimension : 60(w) x 112(h) x 42(d) mm



MMD-214R Wireless Siren + Strobe Light

W/s Tx Distance : 30m (open space)
 Tx Frequency : 433MHz
 Power supply : DC15V
 Power Consumption : Static ~ ≤ 8mA
 Tx ~ ≤ 500mA
 Siren Sound : 110 dB
 Operation Temperature : -10°C ~ 50°C
 Storage Temperature : -20°C ~ 60°C
 Dimension : 128(o) x 40(h) mm



MSR-10W Wireless Siren

W/s Tx Distance : 30m (open space)
 Tx Frequency : 433MHz
 Power Consumption : Static ~ ≤ 8mA
 Tx ~ ≤ 500mA

MSR-10 (Wired) / MSR-10W (wireless) Siren

Power supply : DC12V
 Siren Sound : 110 dB
 Operation Temperature : -10°C ~ 50°C
 Storage Temperature : -20°C ~ 60°C
 Dimension : 128(o) x 40(h) mm