



(Rear view)

Model	FVR – 401
Operation type	Pentaplex (Local Record, Local Playback/Local Settings, Remote Playback/Record, Remote View, Remote Settings)
Video Input / Output	In: 4xBNC, Out: 1xBNC, 1xVGA
Display Mode	1/ 4 ch.
Resolution (max.)	Display: (Composite Video) 704x576 , (VGA) 800x600/ 1024x768Record: (Main)704x576/ 352x576/ 352x288/ 176x144; (Extra) 352x288/ 176x144
Speed (max.)	Display: 100 fps, Record: [Main] 25fps:D1*1+CIF*3 or D1(25fps)*1+D1(5fps)*3 or (Ch1) D1/HD1/CIF/QCIF : 25fps (max.) + (Ch2,Ch3/Ch4)CIF/QCIF : 25fps (max.) [Extra] CIF: 1~5fps, QCIF:1~5fps
Playback channel	1/ 2/ 4 ch.
Record Mode	Manual/ Regular/ Motion
Pre / Post Record Duration	Pre: 1~30 sec.; Post: 2~120 sec.
Search Mode	All/ Alarm/ Motion/ Time/ Date/ Ch.
Video Compression Format	H.264
Image Quality	High / Mid / Low
Audio Input & Output	In: 1xRCA, Out:1xRCA
Alarm Input & Output	-
Motion Detection Area & Sensitivity	Area: 11x9, Sensitivity: 1~6
Privacy Masking	(Each Ch.) 4 x Areas
Console Function	Auto Recover after power resume, Video Loss, Remote Controller, Contrast, Brightness, Colour, Camera On/Off
Hardisc Bay	1 x (SATA)
USB Interface	2xPorts (Ext.HDD, Pendrive backup, PC Mouse, Upgrade)
CDRW / DVDRW	-
PTZ Protocol	Protocol: Pelco-D, Pelco-P, Baud Rate: 1200~38400
Network & Control Interface	RS485
Network Function	PPPoE, NTP, Email, IPFilter, DDNS, PTZ,Full DVR Control, Multi-user login, up to 36ch. Playback
Remote Software	I.E
Power Supply & Consumption	DC12V 2.5A
Operation Temperature & Humidity	10°C ~ 45°C (10%~90%)
Dimension (approximate)	260(w) x 48(h) x 240(d) mm
Weight (w/o Hardisc) (approximate)	1 kg

** Design & specification are subject to change without prior notice **