



**HA - 8200**



(Rear view)

<i>Model</i>	<b>HA – 8200</b>
<i>Operation type</i>	Pentaplex (Local Record, Local Playback/Local Settings, Remote Playback/Record, Remote View, Remote Settings)
<i>Video Input / Output</i>	In: 8xBNC, Out: 1xBNC, 1xVGA
<i>Display Mode</i>	1/ 4/ 9 ch.
<i>Resolution (max.)</i>	<b>Display:</b> (VGA) 640x480/ 800x600/ 1024x768/ 1280x1024/ 1440x900, <b>Record:</b> D1/HD1/CIF
<i>Speed (max.)</i>	<b>Display:</b> 200 fps, <b>Record:</b> (D1)48 fps, (HD1)96 fps, (CIF)200 fps
<i>Playback channel</i>	1/ 4 ch.
<i>Record Mode</i>	Schedule/ Alarm/ Motion
<i>Pre / Post Record Duration</i>	Post : 10 ~ 60sec.
<i>Search Mode</i>	Time/Date, Rec.List, Channel
<i>Video Compression Format</i>	H.264
<i>Image Quality</i>	Highest/ High/ Normal
<i>Audio Input &amp; Output</i>	In: 4xRCA, Out: 1xRCA
<i>Alarm Input &amp; Output</i>	In: 4 ch.(Pin)(NO/NC), Out: 1ch.(Pin)
<i>Motion Detection Area &amp; Sensitivity</i>	<b>Area:</b> 43(H) x 34(V), <b>Sensitivity:</b> 1~10
<i>Privacy Masking</i>	-
<i>Console Function</i>	Display Setup, Record Setup, Network Setup, Mobile Setup
<i>Hardisc Bay</i>	1 x (SATA)
<i>USB Interface</i>	Pendrive, Hardisc Backup, PC Mouse (for control/setting)
<i>CDRW / DVDRW</i>	-
<i>PTZ Protocol</i>	Protocol: 3 types, Baud Rate:1200~19200 bps.
<i>Network &amp; Control Interface</i>	RJ-45, RS485
<i>Network Function</i>	4 users login: (Admin): Full function, (User) Live view; DHCP, Static, PPPoE, DDNS, Email
<i>Remote Software</i>	I.E.
<i>Power Supply &amp; Consumption</i>	DC12V 3.3A
<i>Operation Temperature &amp; Humidity</i>	10°C ~ 45°C (10%~90%)
<i>Dimension (approximate)</i>	300(w) x 50(h) x 220(d) mm
<i>Weight (w/o Hardisc) (approximate)</i>	2.8 kg

\*\* Design & specification are subject to change without prior notice \*\*