



HA - 842



(Rear view)

| | |
|--|---|
| Model | HA - 842 |
| Operation type | Pentaplex (Local Record, Local Playback/Local Settings, Remote Playback/Record, Remote View, Remote Settings) |
| Video Input / Output | In: 8xBNC, Out: 1xBNC, 1xVGA |
| Display Mode | 1/ 4/ 9 ch. |
| Resolution (max.) | Display: (VGA) 640x480/ 800x600/ 1024x768/ 1280x1024/ 1440x900, Record: D1/HD1/CIF |
| Speed (max.) | Display: 200 fps, Record: (D1)48 fps, (HD1)96 fps, (CIF)200 fps |
| Playback channel | 1/ 4 ch. |
| Record Mode | Schedule/ Alarm/ Motion |
| Pre / Post Record Duration | Post : 10 ~ 60sec. |
| Search Mode | Time/Date, Rec.List, Channel |
| Video Compression Format | H.264 |
| Image Quality | Highest/ High/ Normal |
| Audio Input & Output | In: 4xRCA, Out: 1xRCA |
| Alarm Input & Output | In: 4 ch.(Pin)(NO/NC), Out: 1ch.(Pin) |
| Motion Detection Area & Sensitivity | Area: 43(H) x 34(V), Sensitivity: 1~10 |
| Privacy Masking | - |
| Console Function | Display Setup, Record Setup, Network Setup, Mobile Setup |
| Hardisc Bay | 1 x (SATA) |
| USB Interface | Pendrive, Hardisc Backup, PC Mouse (for control/setting) |
| CDRW / DVDRW | - |
| PTZ Protocol | Protocol: 3 types, Baud Rate:1200~19200 bps. |
| Network & Control Interface | RJ-45, RS485 |
| Network Function | 4 users login: (Admin): Full function, (User) Live view; DHCP, Static, PPPoE, DDNS, Email |
| Remote Software | I.E. |
| Power Supply & Consumption | DC12V 3.3A |
| Operation Temperature & Humidity | 10°C ~ 45°C (10%~90%) |
| Dimension (approximate) | 220(w) x 50(h) x 300(d) mm |
| Weight (w/o Hardisc) (approximate) | 2.7 kg |

** Design & specification are subject to change without prior notice **