



(Rear view)

Model	INVR – 0401
Operation type	Pentaplex (Local Record, Local Playback/Local Settings, Remote Playback/Record, Remote View, Remote Settings)
Video Input / Output	In: 4xBNC, Out: 1xBNC, 1xVGA, 1xHDMI
Display Mode	1/ 4 ch
Resolution (max.)	Display: (Composite Video) 704x576 , (VGA) 1920*1080/ 1440*900/1280*1024/ 1280*720/ 1024*768 Record: (Main) 4*D1 (Analog Signal) / 2*1080p (Digital Signal) / Analog+Digital
Speed (max.)	Display: - RealTime - , Record: (Main) 1~25fps; (Extra) (CIF) 1~12fps/ (QCIF) 1~25fps (Analog) D1: 4 ch; (Digital) 1080p: 2 ch./ D1: 9 ch
Playback channel (max.)	Regular/ Detect/ Alarm
Record Mode	Pre: 1~30 sec.; Post: 10~300 sec.
Pre / Post Record Duration	All/ Regular/ Alarm/ Manual/ Intelligent
Search Mode	H.264
Video Compression Format	1 ~ 6
Image Quality	In: 4xRCA, Out: 1xRCA
Audio Input & Output	In: 1xPin, Out: 1xPin(N.O.)
Alarm Input & Output	Area: 16x12, Sensitivity: 1~6
Motion Detection Area & Sensitivity	4 x Areas
Privacy Masking	Individual Channel setting, Auto Recover after power resume, Video Loss, Remote Controller, Fan, Contrast, Brightness, Colour, Dwell time, Camera On/Off
Console Function	1 x (SATA)
Hardisc Bay	2xPort (Ext.HDD, Pendrive backup, PC Mouse, Upgrade)
USB Interface	-
CDRW / DVDRW	Protocol: 21 types, Baud Rate: 1200~115200
PTZ Protocol	RS485
Network & Control Interface	DHCP, PPPoE, FTP, Wifi, DDNS, RTSP, PTZ, Multi-user login
Network Function	IE, CMS
Remote Software	DC12V 3A
Power Supply & Consumption	10°C ~ 45°C (10%~90%)
Operation Temperature & Humidity	345(w) x 70(h) x 230(d) mm
Dimension (approximate)	1.5 kg
Weight (w/o Hardisc) (approximate)	

** Design & specification are subject to change without prior notice **

Recording Resolution Selection Chart

Analog	Digital				Number of Playback Channels
	D1	1080p	720p	960H	
4					4
2	1	1			2
				9	9
			8		8
		4			4
	2				2
		1		7	8
	1	1		2	4
	1				1

** Design & specification are subject to change without prior notice **