



(Rear view)

Model	INVR - 0802
Operation type	Pentaplex (Local Record, Local Playback/Local Settings, Remote Playback/Record, Remote View, Remote Settings)
Video Input / Output	In: 8xBNC, Out: 1xBNC, 1xVGA, 1xHDMI
Display Mode	1/ 4/ 8/ 9 ch.
Resolution (max.)	Display: (Composite Video) 704x576 , (VGA) 1920*1080/ 1440*900/ 1280*1024/ 1280*720/ 1024*768 Record: (Main) 8*960H (Analog Signal) / 8*1080p (HD Digital Signal) / Analog+Digital, [refer to the Rec.Channel Chart]
Speed (max.)	Display: 200 fps, Record: (Main) 1~25fps; (Extra) (CIF/QCIF) 1~25fps
Playback channel (max.)	4~9 ch. [depends on Rec.Channel Type]
Record Mode	Alarm/ Regular/ Motion
Pre / Post Record Duration	Pre: 1~30 sec.; Post: 10~300 sec.
Search Mode	All/ Alarm/ Motion/ Time/ Date/ Ch.
Video Compression Format	H.264
Image Quality	1 ~ 6
Audio Input & Output	In: 1xRCA, Out: 1xRCA
Alarm Input & Output	In: 4xPin, Out: 1xPin(N.O.)
Motion Detection Area & Sensitivity	Area: 16x12, Sensitivity: 1~6
Privacy Masking	4 x Areas
Console Function	Individual Channel setting, Auto Recover after power resume, Video Loss, Remote Controller, Fan, Contrast, Brightness, Colour, Dwell time, Camera On/Off
Hardisc Bay	1 x (SATA)
USB Interface	2xPorts (Ext.HDD, Pendrive backup, PC Mouse, Upgrade)
CDRW / DVDRW	-
PTZ Protocol	Protocol: 21 types, Baud Rate: 1200~115200
Network & Control Interface	RS485
Network Function	DHCP, PPPoE, FTP, Wifi, DDNS, RTSP, PTZ, Multi-user login
Remote Software	IE, CMS
Power Supply & Consumption	DC12V 2A
Operation Temperature & Humidity	10°C ~ 45°C (10%~90%)
Dimension (approximate)	260(w) x 45(h) x 235(d) mm
Weight (w/o Hardisc) (approximate)	1 kg

** Design & specification are subject to change without prior notice **

Recording Resolution Selection Chart

Analog		Digital	Number of Playback Channels
960H	D1	1080p	
	8		4
	8		8
8			2
6		2	1
4		4	1
2		6	2
		8	2

** Design & specification are subject to change without prior notice **