



(Rear view)

Model	INVR – 1602
Operation type	Pentaplex (Local Record, Local Playback/Local Settings, Remote Playback/Record, Remote View, Remote Settings)
Video Input / Output	In: 16xBNC, Out: 1xVGA, 1xHDMI
Display Mode	1/ 4/ 8/ 9/ 16 ch.
Resolution (max.)	Display: (Composite Video) 704x576 , (VGA) 1920*1080/ 1440*900/ 1280*1024/ 1280*720/ 1024*768 Record: (Main) 16*960H (Analog Signal) / 8*1080p (HD Digital Signal) / Analog+Digital (Selectable at Table/Chart in system's Channel Type)
Speed (max.)	Display: 400 fps, Record: (Main) 1~25fps; (Extra) (CIF) 1~12fps/ (QCIF) 1~25fps (Analog) D1*16 ch.; (Digital) 720p HD : 8 ch.
Playback channel (max.)	Alarm/ Regular/ Motion
Record Mode	Pre: 1~30 sec.; Post: 10~300 sec.
Pre / Post Record Duration	All/ Alarm/ Motion/ Time/ Date/ Ch.
Search Mode	H.264
Video Compression Format	1 ~ 6
Image Quality	In: 4xRCA, Out:1xRCA
Audio Input & Output	In: 4xPin, Out:1xPin(N.O.)
Alarm Input & Output	Area: 16x12, Sensitivity: 1~6
Motion Detection Area & Sensitivity	4 x Areas
Privacy Masking	Individual Channel setting, Auto Recover after power resume, Video Loss, Remote Controller, Fan, Contrast, Brightness, Colour, Dwell time, Camera On/Off, PAL/NTSC
Console Function	2 x (SATA)
Hardisc Bay	3xPorts (Ext.HDD, Pendrive backup, PC Mouse, Upgrade)
USB Interface	-
CDRW / DVDRW	Protocol: 21 types, Baud Rate: 1200~115200
PTZ Protocol	RS485, RS232
Network & Control Interface	PPPoE, NTP, Email, IP Filter, DDNS, FTP, ARSP, Alarm Server, Wireless Config, RTSP, Mobile Monitor, IPNP, Wifi, Cloud, PMS, PTZ, Multi-user login
Network Function	IE, CMS
Remote Software	DC12V 4A
Power Supply & Consumption	10°C ~ 45°C (10%~90%)
Operation Temperature & Humidity	325(w) x 55(h) x 260(d) mm
Dimension (approximate)	1.6 kg
Weight (w/o Hardisc) (approximate)	

** Design & specification are subject to change without prior notice **

Recording Resolution Selection Chart

Analog	Digital		Number of Playback Channels
960H	1080p	960H	
16			16 (@ 15fps)
16			8 (@ 25fps)
14	2		1
12	4		2
10	6		4
8	8		4
6		10	4
4		12	4
2		14	4
		16	4

** Design & specification are subject to change without prior notice **