



(Rear view)

<i>Model</i>	INVR - 3202
<i>Operation type</i>	Pentaplex (Local Record, Local Playback/Local Settings, Remote Playback/Record, Remote View, Remote Settings)
<i>Video Input / Output</i>	In: 32xBNC, Out: 2xBNC, 1xVGA, 1xHDMI
<i>Display Mode</i>	(Analog) 1/ 4/ 8/ 16/ 36 ch. ; (Digital) 1/ 10 ch
<i>Resolution (max.)</i>	Display: (Composite Video) 704x576 , (VGA) 1920*1080/ 1440*900/ 1280*1024/ 1280*720/ 1024*768 Record: (Main) : (Analog) 8*D1+24*CIF / (Digital) 4*1080p
<i>Speed (max.)</i>	Display: - RealTime - , Record: (Main) 1~25fps; (Extra) (CIF) 1~12fps/ (QCIF) 1~25fps
<i>Playback channel (max.)</i>	(Analog) 16ch; (Digital) 1080p: 4ch.
<i>Record Mode</i>	Regular/ Detect/ Alarm
<i>Pre / Post Record Duration</i>	Pre: 1~30 sec.; Post: 10~300 sec.
<i>Search Mode</i>	All/ Regular/ Alarm/ Manual/ Intelligent
<i>Video Compression Format</i>	H.264
<i>Image Quality</i>	1 ~ 6
<i>Audio Input & Output</i>	In: 16xRCA, Out:1xRCA
<i>Alarm Input & Output</i>	In: 16xPin, Out:4xPin(N.O.)
<i>Motion Detection Area & Sensitivity</i>	Area: 16x12, Sensitivity: 1~6
<i>Privacy Masking</i>	4 x Areas
<i>Console Function</i>	Individual Channel setting, Auto Recover after power resume, Video Loss, Remote Controller, Fan, Contrast, Brightness, Colour, Dwell time, Camera On/Off
<i>Hardisc Bay</i>	4 x (SATA)
<i>USB Interface</i>	1xPort (Ext.HDD, Pendrive backup, PC Mouse, Upgrade)
<i>CDRW / DVDRW</i>	-
<i>PTZ Protocol</i>	Protocol: 21 types, Baud Rate: 1200~115200
<i>Network & Control Interface</i>	RS485
<i>Network Function</i>	DHCP, PPPoE, FTP, Wifi, DDNS, RTSP, PTZ, Multi-user login
<i>Remote Software</i>	IE, CMS
<i>Power Supply & Consumption</i>	DC12V 6A
<i>Operation Temperature & Humidity</i>	10°C ~ 45°C (10%~90%)
<i>Dimension (approximate)</i>	433(w) x 96(h) x 370(d) mm
<i>Weight (w/o Hardisc) (approximate)</i>	4.5 kg

** Design & specification are subject to change without prior notice **

Recording Resolution Selection Chart

Analog		Digital				Number of Playback Channels
D1	CIF	1080p	720p	960H	D1	
8	24					16
					24	16
				20		16
		4				4
		1	8			9
		2	4	4		10

** Design & specification are subject to change without prior notice **