



**VIB – 301 / 301X**



**VIB – 351**



**VIR - 301**

### Features :-

- Unlimited users login
- Change settings of the IP cam. through internet using I.E. or Client software

	VIB-301	VIB-301 X	VIB-351	VIR-301
<i>Image Sensor</i>	1/3" SONY Colour Super HAD CCD			
<i>Picture Elements</i>	PAL : 500 (H) x 582 (V)			
<i>Resolution</i>	380 TV Line	530 TV Line		380 TV Line
<i>Min. Illumination</i>	0.5 Lux (F 1.2)			0.5 Lux (F1.2), 0 Lux (30 IR On)
<i>Shutter Speed</i>	AES : 1/60 ~ 1/100K sec.			-
<i>Lens Mount</i>	C / CS Mount			6 mm
<i>Back Light Compensation</i>	On / Off selectable			-
<i>Mirror Function</i>	On / Off selectable			-
<i>Auto Iris Control</i>	DC / Video Drive			-
<i>White Balance</i>	-			Auto
<i>Video Output</i>	1 Vp-p Composite (75 ohm)			
<i>Compression Format</i>	MPEG – 4			
<i>Video Resolution</i>	PAL : 720x576, 360x288			
<i>Frame Rate</i>	PAL : 25 fps (max.)			
<i>Image Quality</i>	Best / Super / High / Normal / Middle / Basic			
<i>Alarm Mode</i>	Motion / Sensor Input			
<i>Alarm Triggered Action</i>	Relay Output, Send E-Mail			Send E-Mail
<i>Alarm Input / Output</i>	1x Input, 1x Output (N.O/ N.C)			-
<i>Network / Ethernet</i>	10/100 Base-T, Tj-45			
<i>Protocol Supported</i>	TCP/IP, HTTP, PPPoE, DDNS, DHCP, SMTP, Telnet	TCP/IP, HTTP, PPPoE, DDNS, DHCP, SMTP, Telnet, IEEE802.11g		TCP/IP, HTTP, PPPoE, DDNS, DHCP, SMTP, Telnet
<i>Audio Input</i>	Built-in Mic			-
<i>Audio Output</i>	RCA connector	9-pin connector		-
<i>Motion Detection</i>	Yes ( 9 areas w/selectable sensitivity)			
<i>Security</i>	Password protection			
<i>WEB Encryption</i>	Yes			-
<i>Power Supply</i>	DC 12V 1A	DC 12V 1.25A		DC 12V 1A
<i>Power Consumption (approx.)</i>	9W			7W
<i>Operating Temperature</i>	-5 °C ~ 50°C (23°F ~ 122°F)			-10 °C ~ 50°C (14°F ~ 122°F)
<i>Storage Temperature</i>	-10 °C ~ 60 °C (-4°F ~ 140°F)			-20 °C ~ 60 °C (-4°F ~ 140°F)
<i>Humidity</i>	30 ~ 80%			
<i>Dimension</i>	60(w) x 53(h) x 145(d)			67(o) x 130(d)
<i>Weight</i>	950 g			900 g