



c/w 12*IR LED
LAN+Wifi

VI - 6W



c/w Pan Tilt
LAN

VI - A8

| | VI - A6W | VI - A8 |
|------------------------------|---|----------------------------------|
| Image Pickup Device | 1/6" Colour CMOS | |
| Lens | 2.5 mm | 2.9 mm |
| Horizontal Resolution | 380 TV Line | |
| Pixels | 500(H) x 582(V) | |
| Signal Format | 625 TVLine, 50fps | |
| Illumination | 0 Lux (12*IR On) | 1 Lux |
| IR Coverage | 5 ~ 10m | - |
| S/N Ratio | ≥ 50dB | |
| Gain Control & White Balance | Manual / Auto | |
| Gamma Correction | 0.45 | |
| Electronic Shutter | Auto Exposal : 1/25 ~ 1/15000 | |
| Video Compression | H.264 / MJPEG | |
| Video Resolution | VGA, QVGA, QQVGA, CIF, QCIF | |
| Video Speed | Frame : 1 ~ 25 fps.; Bit : 32K ~ 2Mbps (adjustable) | |
| Image Quality | 6 Levels | |
| Dual Stream | Yes (1ch.D1-20fps + 1ch. CIF-20fps) | |
| Video Motion Detection | 32*18 zones | 16*12 zones |
| Motion Sensitivity | 6 Levels | |
| Audio Input / Output | 1*Mic In., 1*Speaker Out | |
| Audio Compression | G.711/ G.726/ AMR | |
| Audio Bit Rate | 64Kbps/ 32Kbps/ 10.2Kbps | |
| Wireless Network | 802.11b/g | - |
| Local Storage | Builtin Micro SD | |
| Pan Tilt Angle | - | Pan : 0° ~ 130°, Tilt : 0° ~ 70° |
| Pan Tilt Speed | - | 8 Levels (adjustable) |
| Network Support | RJ45, DHCP, SMTP, DDNS, FTP, TCP/IP, IE | |
| User Login | 10 users login simultaneously | |
| Privacy Masking | 8 zones | |
| Operating Temperature | 0°C ~ +50°C | |
| Humidity | 20 ~ 80% | |
| Power Supply | DC 5V 2.5W | DC 5V 3W |
| Dimension (mm) | 90(w)* 75(h)* 60(d) | 110(o)* 110(h) |
| Weight (approx.) | 160 g | 350 g |