



VIB - 101

c/w LAN



c/w 24\*IR LED  
Pan Tilt, LAN

VID - 101

	VI B - 101	VID - 101
Image Pickup Device	1/3" Colour CCD "SONY"	
Lens	-	6 mm
Horizontal Resolution	420 TV Line	
Pixels	500(H) x 582(V)	
Signal Format	625 TVLine, 50fps	
Illumination	0.1 Lux (Colour); 0.01 Lux (B/W)	0 Lux (24*IR LED On)
IR Coverage	-	10 ~ 15m
S/N Ratio	≥ 50dB	
Gain Control & White Balance	Manual / Auto	
Gamma Correction	0.45	
Electronic Shutter	Auto Exposal : 1/25 ~ 1/15000	
Video Compression	H.264 / MJPEG	
Video Resolution	D1 (704*576), HD1 (352*576), CIF (352*288), QCIF (176*144)	
Image Quality	6 Levels	
Dual Stream	Yes (1ch.D1-20fps + 1ch. CIF-20fps)	
Video Speed	1 ~ 25 fps.	
Video Motion Detection	16*19 zones	16*16 zones
Motion Sensitivity	6 Levels	
Audio Input / Output	1*Audio In, 1*Audio Out.	
Audio Compression	G.711/ G.726/ AMR	
Audio Bit Rate	64Kbps/ 32Kbps/ 10.2Kbps	
Local Storage	1*SD slot	
Alarm Input / Output	2*Alarm In, 2*Alarm Out.	
Network Support / Control	RS485,RS232,RJ45, DHCP, SMTP, DDNS, FTP, TCP/IP, PPPoE, IE	
User Login	10 users login simultaneously	
Privacy Masking	8 zones	
Operating Temperature	0°C ~ +50°C	
Humidity	20 ~ 80%	
Power Supply	DC 12V 5W(max)	DC 12V 7W(max)
Dimension (mm)	67(w) x 55(h) x 118(d)	140(o) x 106(h)
Weight (approx.)	500 g	1 kg

\*\* Design & specification are subject to change without prior notice \*\*