

Mini Pinhole Colour Camera



JK - 008A



JK - 009A



JK - 931

	JK-008A	JK-009A	JK-931
Image Pickup Device	1/4" SONY Colour CCD Chipset		
Resolution	420 TV Lines		
Pixels	500(H) x 582(V)		
Lens	3.7 mm (Pin Hole)		3.6 mm
Video Output	1.0 Vp-p 75ohm (BNC type)		
Audio Output	1 ch. (RCA type)		-
Alarm Input / Output	-		
Iris Control	A.E.S.		
Shutter Mode	1/50 ~ 1/100,000 sec.		
S/N Ratio	≥ 48dB (AGC off)		
Gamma Characteristic	0.45		
Scanning System / Frequency	2:1 Interlace; 15.625KHz (H) x 50Hz (V)		
Gain Control / White Balance	Auto		
Backlight Mode	Open		
Minimum Illumination	0.5 Lux		0.2 Lux
Day / Night Function	-		
IR Sensitive	-		
IR LED	-		
IR Coverage / Viewing Range (approximate)	-		
Pan / Tilt Angle (approximate)	-		
Pan / Tilt Speed (approximate)	-		
Image Masking	-		
Aperture Suppress	-		
Flickerless	-		
Sharpness	-		
Built Special Function	-		
Network / Remote Control	-		
Presets	-		
Users	-		
Video Resolution & Speed	-		
Image Quality	-		
Power Supply & Consumption	DC12V 100mA		
Operation Temperature & Humidity	-10°C ~ +50°C ; RH 95% (max.)		
Storage Temperature	-20°C ~ +60°C ; RH 95% (max.)		
Dimension (w/o bracket) (approximate)	15(w) x 15(h) x 15(d) mm	12(w) x 12(h) x 12(d) mm	21(w) x 35(h) x 21(d) mm
Weight (w/o bracket) (approximate)	40 g		50 g

** Design & specification are subject to change without prior notice **