

"MZ" Single-Door Proximity Reader w/Keypad



MZ – 201JE

MZ – 201JE Proximity Reader w/ Keypad

Dimension	:	87(w) x 37(h) x 109(d) mm
Weight	:	150 g (approx.)
Power Supply	:	DC 12V
Power Consump.	:	< 100mA
Frequency	:	2.4GHz
Distance	:	Mifare Card : 30 ~ 80mm EM Card : 80 ~ 150mm
User capacity	:	500 users
Records Capacity:		1000
Output Format	:	Standard Weigand, RS-232
Tx. Distance	:	Weigand(<=200m), RS232(<=15m)
Storage Temper.	:	-40°C ~ +85°C
Operating Temper:		-20°C ~ +60°C
Humidity	:	5% ~ 98%
Input	:	Door contact x 1, Exit button x 1, Fire alarming x 1
Output	:	EM.Lock x 1, Door contact alarm x 1 LED – Green : Working
Working mode	:	i) Card only ii) Card + password iii) Password only
Feature	:	- Easy installation - Simple operation - Stable performance - Excellent security



MZ – 201D8- IP

MZ – 201D8-IP 8ch. Controller

Dimension	:	118(w) x 179(h) x 41(d) mm
Weight	:	500 g (approx.)
Power Supply	:	DC 12V
Comm. interface	:	TCP/IP
Operat. Temper.	:	-20°C ~ +60°C
Humidity	:	5% ~ 90%
Feature	:	- 4 lines LCD - Simple time, attendance function - Export report to matched software
User	:	3072
Store Records	:	11,488