

"MZ" Door Access System



MZ - 7612K Proximity Door Access Keypad

- Power supply: DC12V
- Power consumption: 150 mA
- 500 x User Codes / Cards :
 - 3 User Levels : Normal , Secure, Master, in 2 types of Codes (Primary & Secondary)
- Operating Temperature: -31°C ~ +63°C
- Operating humidity : 0 ~ 95%
- Card detection distance: 65 mm
- Dimension: 76(w)*120(h)*27(d) mm
- Weight : 410 g
- 1 x Aux.In + 1 x Aux.Out.
- 1 x Relay output (N.O / N.C.)
- 1 x Lock output
- Built-in Temper & Bell control
- Mode : **Normal** : Any User with Primary code / card can enter
 - : **Secure** : Only Secure user & Master user can enter
 - Master User : Can enter Primary or Secondary code/card
 - Secure User : Must enter both Primary & Secondary code / Cards (interval <= 10sec.)
- Material : Zinc Alloy
- Dimension : 75(w) x 115(h) x 28(d) mm
- Weight : 280 g

MZ - 7106K Proximity Door Access Keypad

- Power supply: DC12V
- Power consumption: 150 mA
- 2 x User Codes
- 99 Cards
- Operating Temperature: -20°C ~ +55°C
- Operating humidity : 0 ~ 95%
- Card detection distance: 65 mm
- Dimension: 56(w)*95(h)*20(d) mm
- 1 x Relay output (N.O / N.C.)
- 1 x Lock output
- Built-in Temper & Bell control
- Mode : **Normal** : User code #1 or any card holder
 - : **Secure** : Only card user #1 ~ #10 with Valid User Code#1 can enter
- Material : Plastic
- Dimension : 60(w) x 95(h) x 20(d) mm
- Weight : 60 g

