

**4*AHDI+4*720P
Realtime
Display+Record**

**Support Analog & HD,
Normal Analog
IP Cameras**



(Rear view)

Model	NAVR - 0401
Operation type	Pentaplex (Local Record, Local Playback/Local Settings, Remote Playback/Record, Remote View, Remote Settings)
Video Input / Output	In: 4xBNC, Out:1xVGA, 1xHDMI
Display Mode	1/ 4/ 9 ch.
Resolution (max.)	Display: (VGA) 1920*1080/ 1440*900/ 1280*1024/ 1280*720/ 1024*768 Record: (Main) 4*(AHD 1080p), 4*(AHD 720p)+4*(IP HD 720p) (Selectable at Table/Chart in system's Channel Type)
Speed (max.)	Record: (Main Stream) 1~25fps; (ExtraStream) 1~25fps
Playback channel (max.)	(Depend on selection from Table/Chart in system's Channel Type) Max. channels in Live Playback is up to 20 ch.
Record Mode	Alarm/ Regular/ Motion
Pre / Post Record Duration	Pre: 0~30 sec.; Post: 1~120 mins.
Search Mode	All/ Regular/ Alarm/ Motion/ Time/ Date/ Ch.
Video Compression Format	H.264
Image Quality	1 ~ 6
Audio Input & Output	In: 4xRCA, Out: 1xRCA
Alarm Input & Output	-
Motion Detection Area & Sensitivity	Area: 16x12, Sensitivity: 1~6
Privacy Masking	4 x Areas
Console Function	Individual Channel setting, Recorder settings, Auto Recover after power resume
Hardisc Bay	2 x (SATA)
USB Interface	2xPorts (Ext.HDD, Pendrive backup, PC Mouse, Upgrade)
CDRW / DVDRW	-
PTZ Protocol	Protocol: 21 types, Baud Rate: 1200~115200
Network & Control Interface	RS485, Static IP, DHCP, PPPoE, NTP, DDNS, Wireless Config, Mobile, UPNP, Wifi, RTSP, Cloud
Network Function	Full DVR function except for TV +Colour adjust
Remote Software	IE, CMS
Power Supply & Consumption	DC12V 2A
Operation Temperature & Humidity	10°C ~ 45°C (10%~90%)
Dimension (approximate)	260(w) x 45(h) x 230(d) mm
Weight (w/o Hardisc) (approximate)	0.9 kg

** Design & specification are subject to change without prior notice **

Recording Resolution Selection Chart

Analog / Analog HD		Digital			Number of Live Display Channels	Number of Playback Channels
AHD-M (720p)	AHD-L (960H)	1080p	720p	960H		
8					8	8
	8				8	8
8			8		16	8 (selectable)
4			4		8	4 (selectable)
				20	20	16 (selectable)
		4			4	4
		1	8		9	9

** Design & specification are subject to change without prior notice **