



	NK-133
Image Pickup Device	1/3" Colour CMOS
Resolution	400 TV Lines
Pixels	510(H) x 492(V)
Lens	3.6 mm
Video Output	1.0 Vp-p 75ohm (BNC type)
Audio Output	-
Alarm Input / Output	-
Iris Control	A.E.S.
Shutter Mode	1/60 ~ 1/1500 sec.
S/N Ratio	≥ 48dB (AGC off)
Gamma Characteristic	0.45
Scanning System / Frequency	2:1 Interlace; 15.625KHz (H) x 50Hz (V)
Gain Control / White Balance	Auto
Backlight Mode	Open
Minimum Illumination	2 Lux (LED off), 0 Lux (LED on)
Day / Night Function	Yes
IR Sensitive	Yes
IR LED	9xIR LED (2mm)
IR Coverage / Viewing Range (approximate)	2~3m
Pan / Tilt Angle (approximate)	-
Pan / Tilt Speed (approximate)	-
Image Masking	-
Aperture Suppress	-
Flickerless	-
Sharpness	-
Built Special Function	Mirror effect for Reverse car viewing
Network / Remote Control	-
Presets	-
Users	-
Video Resolution & Speed	-
Image Quality	-
Power Supply & Consumption	DC12V 250mA
Operation Temperature & Humidity	-20°C ~ +50°C ; RH 95% (max.)
Storage Temperature	-20°C ~ +60°C ; RH 95% (max.)
Dimension (w/o bracket) (approximate)	37(w) x 25(h) x 37(d) mm
Weight (w/o bracket) (approximate)	50 g

** Design & specification are subject to change without prior notice **