

Vzortech Colour Nightvision Camera



| | NR - 102 |
|--|---|
| Image Pickup Device | 1/3" SONY Colour CCD Chipset |
| Resolution | 420 TV Lines |
| Pixels | 628(H) x 582(V) |
| Lens | 3.6 mm |
| Video Output | 1.0 Vp-p 75ohm (BNC type) |
| Audio Output | - |
| Alarm Input / Output | - |
| Iris Control | A.E.S. |
| Shutter Mode | On |
| S/N Ratio | ≥ 48dB (AGC off) |
| Gamma Characteristic | 0.45 |
| Scanning System / Frequency | 2:1 Interlace; 15.625KHz (H) x 50Hz (V) |
| Gain Control / White Balance | Auto |
| Backlight Mode | Open |
| Minimum Illumination | 0.8 Lux (LED off), 0 Lux (LED on) (F:1.2) |
| Day / Night Function | Yes |
| IR Sensitive | Yes |
| IR LED | 30xIR LED (5mm) |
| IR Coverage / Viewing Range (approximate) | 15~20m |
| Pan / Tilt Angle (approximate) | - |
| Pan / Tilt Speed (approximate) | - |
| Image Masking | - |
| Aperture Suppress | - |
| Flickerless | - |
| Sharpness | - |
| Built Special Function | - |
| Network / Remote Control | - |
| Presets | - |
| Users | - |
| Video Resolution & Speed | - |
| Image Quality | - |
| Power Supply & Consumption | DC12V 500mA |
| Operation Temperature & Humidity | -10°C ~ +50°C ; RH 85% (max.) |
| Storage Temperature | -20°C ~ +60°C ; RH 85% (max.) |
| Dimension (w/o bracket) (approximate) | 75(w) x 65(h) x 123(d) mm |
| Weight (w/o bracket) (approximate) | 350 g |

** Design & specification are subject to change without prior notice **