

neo V

4 / 8 ch. Pentaplex DVR



NVR - 0401

(Rear view)



NVR - 0801

Model

Operation type

Video Input / Output

Display Mode

Resolution (max.)

Speed (max.)

Playback channel

Record Mode

Pre / Post Record Duration

Search Mode

Video Compression Format

Image Quality

Audio Input & Output

Alarm Input & Output

Motion Detection Area & Sensitivity

Privacy Masking

Console Function

Hardisc Bay

USB Interface

CDRW / DVDRW

PTZ Protocol

Network & Control Interface

Network Function

Remote Software

Power Supply & Consumption

Operation Temperature & Humidity

Dimension (approximate)

Weight (w/o Hardisc) (approximate)

NVR - 0401

NVR - 0801

Pentaplex (Local Record, Local Playback/Local Settings, Remote Playback/Record, Remote View, Remote Settings)

In: 4xBNC,
Out: 1xBNC

In: 8xBNC,
Out: 2xBNC, 1xVGA

1/ 4 ch.

1/ 4/ 9 ch.

Display: (VGA) 1024x768/ 800x600, Record: D1/ HD1/ CIF

Display: 100 fps,

Display: 200 fps,

Record: 100fps

Record: 200 fps

1/ 4 ch.

1/ 4/ 8 ch.

Power Up/Timer/ Motion

Pre: 10sec.; Post : 30sec./ 1min./ 2min./ 5min.

Time / Date / Event/ Channel

H.264

Highest/ High/ Normal

In: 4xRCA, Out:1xRCA

In: 8xRCA, Out:1xRCA

In: 8 ch.(Pin),

Out: 1ch.(Pin) (NO):

Duration:10~60sec.

Area: 13(H) x 10(V), Sensitivity:1~4

Each Channel: Area: 16x13

Display Setup, Record Setup, Network Setup, Mobile Setup

1 x (SATA)

Pendrive, Hardisc Backup, PC Mouse (for control/setting), Software upgrade

Pelco-D/ Pelco-P, Baud Rate:1200~9600bps.

RJ-45, RS232, RS485

Multiple users login: Priority(Admin/User), Admin: Full function of DVR settings, Static, DHCP, PPPoE, DDNS, Email

I.E.

DC19V 3A

10°C ~ 45°C (10%~90%)

300(w) x 55(h) x 235(d) mm

3 kg

3.2 kg

** Design & specification are subject to change without prior notice **