

neoV

4 ch. Pentaplex DVR



(Rear view)

Model	NVR - 042
Operation type	Pentaplex (Local Record, Local Playback/Local Settings, Remote Playback/Record, Remote View, Remote Settings)
Video Input / Output	In: 4x BNC, Out: 1x BNC, 1x VGA
Display Mode	1/ 4 ch.
Resolution (max.)	Display: 1280x1024/ 1280x720/ 1024x768/ 800x600, Record: 704x576
Speed (max.)	Display: 100 fps, Record: D1: [1*(1~25fps) + 3*(1~6fps)] + CIF :1~25fps + QCIF :1~25fps (Total:100fps)
Playback channel	4 ch
Record Mode	Manual / Timer / Motion / Alarm
Pre / Post Record Duration	Pre: 1 ~ 30 sec., Post : 10 ~ 300 sec.
Search Mode	Time / Date / Motion / Alarm
Video Compression Format	H.264
Image Quality	VBR : 1 ~ 6
Audio Input & Output	In: 2x BNC, Out: 1x BNC
Alarm Input & Output	In: 4 ch.(Pin), Out: 1ch.(Pin) (N.O.)
Motion Detection Area & Sensitivity	Area: 22(H) x 18(V), Sensitivity:1~6
Privacy Masking	4 Areas (Each channel, during preview / monitoring)
Console Function	Channel Lock, Partial display enlargement, Auto Recover after power resume, Hardisc redundant, TV display adjust, Colour, Hue, Brightness, Contrast, Gain, White Level, Email/Pop-up message/Relay out/PTZ/Ch.Rec. for any triggered events, Each channel can choose to record Audio+Video or only Audio/Video, Extra Stream for recording/playback
Hardisc Bay	1 x (SATA)
USB Interface	Pendrive, Hardisc Backup, PC Mouse (for control/setting)
CDRW / DVDRW	-
PTZ Protocol	35 types, Baud Rate:1200~115200bps.
Network & Control Interface	RJ-45, RS485
Network Function	Multi-users login, full function of DVR settings, PPPoE, NTP, Multicast, Email, IP Filter
Remote Software	I.E.
Power Supply & Consumption	DC12V 3.3A
Operation Temperature & Humidity	10°C ~ 45°C (10%~90%)
Dimension (approximate)	375(w) x 50(h) x 285(d) mm
Weight (w/o Hardisc) (approximate)	3 kg

** Design & specification are subject to change without prior notice **