

neo V

4 ch. DVR



(Rear view)

Model	NVR-043
Operation type	Triplex (Playback, Record, Network)
Video Input / Output	In: 4xBNC, Out: 2xBNC, 1xVGA
Display Mode	1/ 4 ch.
Resolution (max.)	Display: (Composite Video) 704x576 , (VGA) 800x600/ 1024x768/ 1280x1024/ 1360x768/ 1440x900 Record: 704x576
Speed (max.)	Display: 100 fps, Record: D1 :(1~11fps) +/-or HD1 :(1~22fps) +/-or CIF :(1~25fps) +/-or QCIF (1~25fps)
Playback channel	1/ 4 ch.
Record Mode	Alarm/ Manual/ Schedule/ Motion
Pre / Post Record Duration	Pre: 1~30 sec.; Post: 1~120 sec.
Search Mode	Time / Date / Event
Video Compression Format	H.264
Image Quality	VBR : Worst/Worse/General/Good/Better/Best; CBR :Good
Audio Input & Output	In: 1xRCA, Out:1xRCA
Alarm Input & Output	In: 4xPin, Out: 1xPin(N.O)
Motion Detection Area & Sensitivity	Area : 22x16, Sensitivity : Lowest/Lower/Middle/ High/Higher/ Highest
Privacy Masking	-
Console Function	Auto Recover after power resume, Video Loss, Remote Controller, Fan, Contrast, Brightness, Colour, Dwell time, Camera On/Off
Hardisc Bay	1 x (SATA)
USB Interface	HDD, Pendrive backup, PC Mouse, Upgrade
CDRW / DVDRW	-
PTZ Protocol	Protocol: 17 types, Baud Rate: 1200~115200
Network & Control Interface	RS485
Network Function	PPPoE, NTP, Email, IPFilter, DDNS, PTZ,Full DVR Control, Multi-user login
Remote Software	I.E
Power Supply & Consumption	DC12V 4A
Operation Temperature & Humidity	10°C ~ 45°C (10%~90%)
Dimension (approximate)	250(w) x 50(h) x 215(d) mm
Weight (w/o Hardisc) (approximate)	2 kg

** Design & specification are subject to change without prior notice **