



(Rear view)

<b>Model</b>	<b>NVR - 0804</b>
<b>Operation type</b>	Pentaplex (Local Record, Local Playback/Local Settings, Remote Playback/Record, Remote View, Remote Settings)
<b>Video Input / Output</b>	In: 8xBNC, Out: 1xBNC, 1xVGA
<b>Display Mode</b>	1/ 4/ 8/ 9 ch.
<b>Resolution (max.)</b>	Display: (Composite Video) 704x576, (VGA) 800x600/ 1024x768/ 1280x1024/ 1360x768/ 1440x900 Record: (Main) [ 2*D1/HD1+6*CIF/QCIF ] or [ 8*CIF/QCIF ]; (Extra) 8*QCIF
<b>Speed (max.)</b>	Display: 200 fps, Record: (Main) D1/ HD1/ CIF/ QCIF : 1~25fps; (Extra) QCIF:1~25fps
<b>Playback channel</b>	1/ 2/ 4/ 9 ch.
<b>Record Mode</b>	Alarm/ Manual/ Regular/ Motion
<b>Pre / Post Record Duration</b>	Pre: 1~30 sec.; Post: 10~300 sec.
<b>Search Mode</b>	All/ Alarm/ Motion/ Time/ Date/ Ch.
<b>Video Compression Format</b>	H.264
<b>Image Quality</b>	1 ~ 6
<b>Audio Input &amp; Output</b>	In: 1xRCA, Out:1xRCA
<b>Alarm Input &amp; Output</b>	In: 1xPin, Out: 1xPin(N.O.)
<b>Motion Detection Area &amp; Sensitivity</b>	<b>Area:</b> 16x12, <b>Sensitivity:</b> 1~6
<b>Privacy Masking</b>	4 x Areas
<b>Console Function</b>	Auto Recover after power resume, Video Loss, Remote Controller, Fan, Contrast, Brightness, Colour, Dwell time, Camera On/Off
<b>Hardisc Bay</b>	1 x (SATA)
<b>USB Interface</b>	2xPorts (Ext.HDD, Pendrive backup, PC Mouse, Upgrade)
<b>CDRW / DVDRW</b>	-
<b>PTZ Protocol</b>	Protocol: 20 types, Baud Rate: 1200~115200
<b>Network &amp; Control Interface</b>	RS485
<b>Network Function</b>	PPPoE, NTP, Email, IPFilter, DDNS, PTZ,Full DVR Control, Multi-user login, up to 64ch. Playback
<b>Remote Software</b>	I.E
<b>Power Supply &amp; Consumption</b>	DC12V 2.5A
<b>Operation Temperature &amp; Humidity</b>	10°C ~ 45°C (10%~90%)
<b>Dimension (approximate)</b>	260(w) x 50(h) x 240(d) mm
<b>Weight (w/o Hardisc) (approximate)</b>	1.1 kg

\*\* Design & specification are subject to change without prior notice \*\*