



(Rear view)

<b>Model</b>	<b>NVR - 0805</b>
<b>Operation type</b>	Pentaplex (Local Record, Local Playback/Local Settings, Remote Playback/Record, Remote View, Remote Settings)
<b>Video Input / Output</b>	In: 8xBNC, Out: 1xBNC, 1xVGA, 1xHDMI
<b>Display Mode</b>	1/ 4/ 9 ch.
<b>Resolution (max.)</b>	Display: (Composite Video) 704x576 , (VGA) 1024x768/ 1280x720/ 1280x1024/ 1440x900/ 1920x1080 Record: (Main) [ 2*D1/HD1+6*CIF/QCIF ] or [ 8*CIF/QCIF ]; (Extra) 8*CIF/QCIF
<b>Speed (max.)</b>	Display: 200 fps, Record: (Main) D1/ HD1/ CIF: 1~25fps; (Extra) CIF/QCIF:1~25fps
<b>Playback channel</b>	1/ 2/ 4/ 9 ch.
<b>Record Mode</b>	Regular/ Motion/ Alarm/ Schedule/ Manual
<b>Pre / Post Record Duration</b>	Pre: 1~30 sec.; Post: 10~300 sec.
<b>Search Mode</b>	All/ Regular/ Motion/ Alarm/ Time/ Date/ Channel/ Next File/ Previous File
<b>Video Compression Format</b>	H.264
<b>(Bit Rate) Image Quality</b>	(VBR) 6 types; (CBR) Selectable Bit Rate depends on resolution & rec.speed
<b>Audio Input &amp; Output</b>	In: 1xRCA, Out:1xRCA
<b>Alarm Input &amp; Output</b>	-
<b>Motion Detection Area &amp; Sensitivity</b>	<b>Area:</b> 16x12, <b>Sensitivity:</b> 1~6
<b>Privacy Masking</b>	-
<b>Console Function</b>	Auto Recover after power resume, Video Loss, Remote Controller, Fan, Contrast, Brightness, Colour, Dwell time, Camera On/Off
<b>Hardisc Bay</b>	1 x (SATA)
<b>USB Interface</b>	2xPorts (Ext.HDD, Pendrive backup, PC Mouse, Upgrade)
<b>CDRW / DVDRW</b>	-
<b>PTZ Protocol</b>	Protocol: 21 types, Baud Rate: 1200~115200
<b>Network &amp; Control Interface</b>	RS485
<b>Network Function</b>	PPPoE, NTP, DDNS, FTP, ARSP, UPNP, RSTP, Cloud, PMS, Email, IPFilter, PTZ,Full DVR Control, Multi-user login
<b>Remote Software</b>	IE
<b>Power Supply &amp; Consumption</b>	DC12V 2A
<b>Operation Temperature &amp; Humidity</b>	10°C ~ 45°C (10%~90%)
<b>Dimension (approximate)</b>	250(w) x 50(h) x 223(d) mm
<b>Weight (w/o Hardisc) (approximate)</b>	1 kg

\*\* Design & specification are subject to change without prior notice \*\*