



NVR - 1601



(Rear view)

Model	NVR - 1601
Operation type	Pentaplex (Local Record, Local Playback/Local Settings, Remote Playback/Record, Remote View, Remote Settings)
Video Input / Output	In: 16xBNC, Out: 2xBNC, 1xVGA
Display Mode	1/ 4/ 9/ 16 ch./ PIP: 1x1 / 1x2
Resolution (max.)	Display: (VGA) 1024x768/ 800x600, Record: (CIF) 352x288
Speed (max.)	Display: 400 fps, Record: 400 fps
Playback channel	1/ 4 ch.
Record Mode	Schedule / Timer / Motion/ Always
Pre / Post Record Duration	Pre: 10sec.; Post : 30sec./ 1min./ 2min./ 5min.
Search Mode	Time / Date / Event/ Channel
Video Compression Format	H.264
Image Quality	Good/ Mid/ Low (Each channel selectable)
Audio Input & Output	In: 16xRCA, Out: 1xRCA
Alarm Input & Output	In: 16 ch.(Pin), Out: 2 ch.(Pin) (NO):Duration:10~60sec.
Motion Detection Area & Sensitivity	Each Channel: Area: 13(H) x 10(V), Sensitivity:1~4
Privacy Masking	-
Console Function	Display Colour Setup, Record Setup, Network Setup, Mobile Setup
Hardisc Bay	2 x (SATA)
USB Interface	Pendrives, Hardisc Backup, PC Mouse (for control/setting), Software upgrade
CDRW / DVDRW	-
PTZ Protocol	Pelco-D/ Pelco-P, Baud Rate:1200~9600bps.
Network & Control Interface	RJ-45, RS232, RS485
Network Function	Multiple users login: Priority(Admin/User), Admin: Full function of DVR settings, Static, DHCP, PPPoE, DDNS, Static, Email
Remote Software	I.E.
Power Supply & Consumption	DC19V 3A
Operation Temperature & Humidity	10°C ~ 45°C (10%~90%)
Dimension (approximate)	405(w) x 65(h) x 315(d) mm
Weight (w/o Hardisc) (approximate)	4 kg

** Design & specification are subject to change without prior notice **