



(Rear view)

Model	NVR - 1604
Operation type	Pentaplex (Local Record, Local Playback/Local Settings, Remote Playback/Record, Remote View, Remote Settings)
Video Input / Output	In: 16x BNC, Out: 1x BNC
Display Mode	1 / 4 / 8 / 9 / 16 ch.
Resolution (max.)	Display: (Composite Video) 704x576, (VGA) 800x600 / 1024x768 / 1280x1024 / 1360x768 / 1440x900 Record: (Main) 352x288; (Extra) 352x288 / 176x144
Speed (max.)	Display: 400 fps, Record: (Main) CIF (1~25fps); (Extra) CIF: 1~9fps, QCIF: 1~25fps
Playback channel	1 / 2 / 4 / 9 / 16 ch.
Record Mode	Alarm / Manual / Regular / Motion
Pre / Post Record Duration	Pre: 1~30 sec.; Post: 10~300 sec.
Search Mode	All / Alarm / Motion / Time / Date / Ch.
Video Compression Format	H.264
Image Quality	1 ~ 6
Audio Input & Output	In: 4x RCA, Out: 1x RCA
Alarm Input & Output	In: 4x, Out: 1x
Motion Detection Area & Sensitivity	Area: 16x12, Sensitivity: 1~6
Privacy Masking	4 x Areas
Console Function	Auto Recover after power resume, Video Loss, Remote Controller, Fan, Contrast, Brightness, Colour, Dwell time, Camera On/Off
Hardisc Bay	2 x (SATA)
USB Interface	2x Ports (Ext. HDD, Pendrive backup, PC Mouse, Upgrade)
CDRW / DVDRW	-
PTZ Protocol	Protocol: 21 types, Baud Rate: 1200~115200
Network & Control Interface	RS485
Network Function	PPPoE, NTP, Email, IP Filter, DDNS, FTP, ARSP, Alarm Server, Wireless Config, RTSP, Mobile Monitor, IPNP, Wifi, Cloud, PMS, PTZ, Multi-user login
Remote Software	IE
Power Supply & Consumption	DC12V 4A
Operation Temperature & Humidity	10°C ~ 45°C (10%~90%)
Dimension (approximate)	325(w) x 58(h) x 235(d) mm
Weight (w/o Hardisc) (approximate)	1.5 kg

** Design & specification are subject to change without prior notice **