

# neoV

## 9 ch. DVR



(Rear view)

<b>Model</b>	<b>NVR-979</b>
<b>Operation type</b>	Simplex (Playback / Record / Networking)
<b>Video Input / Output</b>	In: 9xBNC, Out: 1xBNC
<b>Display Mode</b>	1/ 4/ 9 ch.
<b>Resolution (max.)</b>	Display: 720x480, Record: 704x508
<b>Speed (max.)</b>	Display: 225 fps, Record: 50 fps
<b>Playback channel</b>	1 ch.
<b>Record Mode</b>	Timer / Motion
<b>Pre / Post Record Duration</b>	Post : >= 10 sec.
<b>Search Mode</b>	Time / Date / Event
<b>Video Compression Format</b>	Local: Modified MJPEG, Network: MPEG4
<b>Image Quality</b>	Low / Normal / High / Highest
<b>Audio Input &amp; Output</b>	In: 1xRCA, Out: 1xRCA
<b>Alarm Input &amp; Output</b>	In: 8ch.(Pin), Out: 1ch.(Pin)(NO/NC)
<b>Motion Detection Area &amp; Sensitivity</b>	Area: 21x12, Sensitivity: 1(Low) ~ 3(High)
<b>Privacy Masking</b>	-
<b>Console Function</b>	Auto Recover after power resume, Video Loss, Hide Live Display, Remote Controller, Fan, Contrast, Brightness, Colour, Dwell time, Camera On/Off
<b>Hardisc Bay</b>	1 x (SATA)
<b>USB Interface</b>	Pendrive, HDD backup, MCG
<b>CDRW / DVDRW</b>	-
<b>PTZ Protocol</b>	Pelco-D, Pelco-P, Baud Rate: 1200~19200bps.
<b>Network &amp; Control Interface</b>	RJ45, RS485,
<b>Network Function</b>	2 types of user, Multi users login, Playback, Record, DVR settings, TCP/IP, PPPoE, DHCP, DDNS
<b>Remote Software</b>	I.E., Client Software
<b>Power Supply &amp; Consumption</b>	DC12V 4A
<b>Operation Temperature &amp; Humidity</b>	10°C ~ 45°C (10%~90%)
<b>Dimension (approximate)</b>	345(w) x 70(h) x 230(d) mm
<b>Weight (w/o Hardisc) (approximate)</b>	3 kg

\*\* Design & specification are subject to change without prior notice \*\*