

Quad - Multiplexer



VO - 403



VQ - 1601 S



VQ - 6408



MV-99E

Selectable no. of camera display on screen :

- (VQ-403) 1/2/4, PIP cameras – selectable/changeable (with Zoom function)
(VQ-6408) 1/4/2*4 cameras – selectable/changeable (with Zoom function)
(MV-99E) 1/4/9 cameras – selectable/changeable (with Zoom function)
(VQ-1601S) 1/4/9/13/16 cameras – selectable/changeable (with Zoom function)

Video input:

- (VQ-403) =4*Video In., (VQ-43) =8*Video In.,
(MV-99E) =9*Video In., (VQ-1601S) =16*Video In.,
1.0 Vp-p, 75 ohms terminated, BNC female connector
1 VCR playback input : 1.0 Vp-p, 75 Ohms terminated, BNC female connector
1 S-VHS Y/C output

Video output:

- 1 monitor output : 1.0 Vp-p, 75 Ohms loaded, BNC female connector
1 call monitor output : 1.0 Vp-p, 75 Ohms loaded, BNC female connector
1 VCR output : 1.0Vp-p 75 Ohms loaded, BNC female connector
1 S-VHS Y/C output

Resolution: (NTSC) 720 x 480; (PAL) 768 x 512

Motion sensing: 16H x 12V(192 Grid) *(Only for MV-99E)*

Alarm input: *(Only for MV-99E)*

1/ 4/ 8/ 9 / 16 dry contact alarm inputs
+5 to +15 VDC or TTL/CMOS signal, DB-25 female connector

Alarm output: *(Only for MV-99E)*

1 normally open (NO) alarm contact : DB-25 female connector
1 normally closed (NC) alarm contact : DB-25 female connector
2 A/30 VDC or 1A/120 VAC resistive load

Alarm duration: 1-99 seconds, programmable *(Only for MV-99E)*

Operating temperature: 5°C to 45°C