

SONY Network Camera



SNC – M1
SNC – M1 W (c/w Wifi)



SNC – M3 (Pan Tilt)
SNC – M3 W (c/w Wifi + Pan Tilt)

	SNC – M1	SNC – M1W	SNC – M3	SNC – M3W
<i>Image Pickup Sensor</i>	1/4" CMOS (Colour)			
<i>Effective Pixel</i>	652 x 482			
<i>Lens</i>	3.7mm Board Lens			
<i>Viewing Angle</i>	(H) 51°C ; (V)38.9°C			
<i>Pan Angle</i>	-	-	+60° ~ -60°	
<i>Tilt Angle</i>	-	-	+10° ~ -60°	
<i>Min. Object Distance</i>	80cm (32")			
<i>Min. Illumination</i>	4.5 Lux (AGC On)			
<i>Compression Format</i>	Mpeg-4, Jpeg			
<i>Image Side</i>	640x480, 320x249, 160x120			
<i>Max. Frame Rate</i>	30 fps			
<i>Audio Compression</i>	G.726 (40,32,24,16kps)			
<i>Builtin Microphone</i>	Electret Condensor Mic			
<i>Protocols</i>	TCP/IP, ARP, ICMP, DHCP, DNS, HTTP, FTP, SMTP, NTP			
<i>Input/Output</i>	RJ45*1, Mic In*1, Audio Out*1			
<i>Weight</i>	250 g	280 g	350 g	380 g
<i>Dimension</i>	110(o) x 68.5(h) mm		110(o) x 104(h) mm	
<i>Power Supply & Cons.</i>	DC 5V (2.9W)	DC 5V (5.2W)	DC 5V (5.5W)	DC 5V (8.2W)
<i>Operate. Temperature</i>	0°C ~ 40°C			
<i>Storage Temperature</i>	-20°C ~ 60°C			
<i>System Requirements</i>	MS-Windows 2000/XP, INTEL P3 1GHz or higher (P4 2GHz Recommended), 256MB RAM(min.), I.E. v5.5 or higher			

** Design & specification are subject to change without prior notice **