



NSD-01	
<i>Image Pickup Device</i>	1/4" SONY Super HAD Colour CCD
<i>Resolution</i>	520 TV Lines
<i>Pixels</i>	752(H) x 582(V)
<i>Lens</i>	10x Optical Zoom (f=3.78~37.8mm)
<i>Video Output</i>	1.0 Vp-p 75ohm (BNC type)
<i>Audio Output</i>	-
<i>Alarm Input / Output</i>	-
<i>Iris Control</i>	Auto / Manual
<i>Shutter Mode</i>	1/50 ~ 1/100,000 sec.
<i>S/N Ratio</i>	≥ 50dB (AGC off)
<i>Gamma Characteristic</i>	-
<i>Scanning System & Frequency</i>	15.625KHz (H) x 50Hz (V)
<i>Gain Control & White Balance</i>	Gain Control: Auto; White Balance: Auto/ PUSH/ MANU/ INDR/ FLUO/ OUTD
<i>Backlight Mode</i>	5 Areas
<i>Minimum Illumination</i>	1 Lux
<i>Day / Night Function</i>	Yes
<i>IR Sensitive</i>	-
<i>IR LED</i>	-
<i>IR Coverage / Viewing Range (approximate)</i>	-
<i>Pan / Tilt Angle (approximate)</i>	Pan: 360° (continuously), Tilt: 0~90°
<i>Pan / Tilt Speed (approximate)</i>	Pan: (Manual) 1.5~120°/sec.,(Auto) 1.5~240°/sec., Tilt: (Manual) 1.5~120°/sec.,(Auto) 1.5~240°/sec.
<i>Image Masking</i>	8 Zones
<i>Aperture Suppress</i>	Yes
<i>Flickerless</i>	Yes
<i>Sharpness</i>	Low/ Mid/ High/ Off
<i>Built Special Function</i>	Auto Exposure : Auto/ Brightne/ Shutter/ Iris, Focus: Auto/ Manual/ INTV/ ZMTR, Mirror: On/ Off, Anti Colour Rolling
<i>Network / Remote Control</i>	RS-485
<i>Address / Presets / Protocol</i>	Address: 256, Preset: 160, Protocol: 6 (BaudRate: 2400~19200bps)
<i>Users</i>	-
<i>Video Resolution & Speed</i>	-
<i>Image Quality</i>	-
<i>Power Supply & Consumption</i>	DC12V
<i>Operation Temperature & Humidity</i>	-10°C ~ +50°C ; RH 95% (max.)
<i>Storage Temperature</i>	-20°C ~ +60°C ; RH 95% (max.)
<i>Dimension (w/o bracket) (approximate)</i>	160(Φ) x 151(h) mm
<i>Weight (w/o bracket) (approximate)</i>	2 kg