

VZOR

IP SpeedDome

**VISD - 01****360° Turning (Pan)**

	VISD - 01
<i>Image Pickup Device</i>	1/4" Colour CCD "HITACHI"
<i>Lens</i>	23x Optical Zoom (10x Digital Zoom)
<i>Horizontal Resolution</i>	480 TV Line
<i>Pixels</i>	PAL : 752(H) x 582(V)
<i>Signal Format</i>	PAL : 625 TVLine, 50fps
<i>Video Output</i>	0.2Vp-p 75Ω
<i>Illumination</i>	0.07 Lux
<i>S/N Ratio</i>	≥ 50dB
<i>Gain Control & White Balance</i>	Manual / Auto
<i>Alarm Input / Output</i>	2 x Alarm In., 1 x Alarm Out. (DC30V 1A)
<i>PanTilt Angle</i>	(Pan) 360°, (Tilt) 90°~180°
<i>Pan Speed</i>	(Manual) 0.1° ~ 120° sec., (Auto) 300° sec.
<i>Tilt Speed</i>	(Manual) 0.1° ~ 90° sec., (Auto) 0° ~ 180° sec.
<i>PTZ Scan Accuracy</i>	0.06 ± 0.015°
<i>Built-in Presets</i>	80* preset positions, 8* Auto tours, 1* Auto Scan, 5* Auto Pattern
<i>Network Support</i>	RS485, DHCP, SMTP, DDNS, FTP, TCP/IP, Multiple protocol, IE
<i>Baud Rate</i>	1200/ 2400/ 4800/ 9600
<i>User Login</i>	10 users login simultaneously
<i>Privacy Masking</i>	8 Zones
<i>Video Compression</i>	H.264 (MPEG-4 PT.10)
<i>Video Resolution</i>	D1, HD1, CIF, QCIF
<i>Video Speed</i>	PAL : 1 ~ 25 fps.
<i>Image Quality</i>	6 Levels (adjustable)
<i>Fan & Heater</i>	Auto / Manual
<i>Operating Temperature</i>	-30°C ~ +55°C
<i>Humidity</i>	< 90%
<i>Power Supply</i>	AC 24v 3A
<i>Core Consumption</i>	15W
<i>Heater Consumption</i>	35W
<i>Dimension (mm)</i>	240(o)* 275(h)
<i>Weight (approx.)</i>	4 kg

** Design & specification are subject to change without prior notice **