



	VSD-01	VSD-02	VSD-101
<b>Image Pickup Device</b>	1/4" Hitachi Colour CCD	1/4" SONY Colour CCD	
<b>Resolution</b>	480 TV Lines		
<b>Pixels</b>	752(H) x 582(V)		
<b>Lens</b>	22x Optical Zoom (f=4~88mm)	26x Optical Zoom (f=3.5~91mm)	
<b>Video Output</b>	1.0 Vp-p 75ohm (BNC type)		
<b>Audio Output</b>	-		
<b>Alarm Input / Output</b>	-		
<b>Iris Control</b>	Auto / Manual		
<b>Shutter Mode</b>	-		
<b>S/N Ratio</b>	≥ 50dB (AGC off)		
<b>Gamma Characteristic</b>	-		
<b>Scanning System &amp; Frequency</b>	15.625KHz (H) x 50Hz (V)		
<b>Gain Control &amp; White Balance</b>	Auto / Manual		
<b>Backlight Mode</b>	-		
<b>Minimum Illumination</b>	0.1 Lux	0.01 Lux	
<b>Day / Night Function</b>	-	Yes	
<b>IR Sensitive</b>	-		
<b>IR LED</b>	-		
<b>IR Coverage / Viewing Range (approximate)</b>	-		
<b>Pan / Tilt Angle (approximate)</b>	<b>Pan:</b> 360° (continuously), <b>Tilt:</b> 0~90°		
<b>Pan / Tilt Speed (approximate)</b>	<b>Pan:</b> 0~12°/sec., <b>Tilt:</b> 0~15°/sec.		<b>Pan:</b> 0~80°/sec., <b>Tilt:</b> 0~40°/sec.
<b>Image Masking</b>	-		
<b>Aperture Suppress</b>	-		
<b>Flickerless</b>	-		
<b>Sharpness</b>	-		
<b>Built Special Function</b>	Heater + Fan		
<b>Network / Remote Control</b>	RS-485		
<b>Address / Presets / Protocol</b>	<b>Address:</b> 1024, <b>Presets:</b> 64, <b>Protocol:</b> 18 (BaudRate: 2400~19200bps)		
<b>Users</b>	-		
<b>Video Resolution &amp; Speed</b>	-		
<b>Image Quality</b>	-		
<b>Power Supply &amp; Consumption</b>	AC24V 1.7A		
<b>Operation Temperature &amp; Humidity</b>	-10°C ~ +50°C ; RH 95% (max.)		
<b>Storage Temperature</b>	-20°C ~ +60°C ; RH 95% (max.)		
<b>Dimension (w/o bracket) (approximate)</b>	234(Φ) x 347(h) mm		
<b>Weight (w/o bracket) (approximate)</b>	4.5 kg		

\*\* Design & specification are subject to change without prior notice \*\*