



	VSD-301
Image Pickup Device	1/4" VZOR Super Colour CCD
Resolution	480 TV Lines
Pixels	752(H) x 596(V)
Lens	18x Optical Zoom (f=4.1~73.8mm)
Video Output	1.0 Vp-p 75ohm (BNC type)
Audio Output	-
Alarm Input / Output	-
Iris Control	Auto / Manual
Shutter Mode	1/50 ~ 1/120,000 sec.
S/N Ratio	≥ 50dB (AGC off)
Gamma Characteristic	-
Scanning System & Frequency	15.625KHz (H) x 50Hz (V)
Gain Control & White Balance	Auto / Manual
Backlight Mode	-
Minimum Illumination	Colour: 1 Lux, B/W: 0.05 Lux
Day / Night Function	Yes
IR Sensitive	-
IR LED	-
IR Coverage / Viewing Range (approximate)	-
Pan / Tilt Angle (approximate)	Pan: 360° (continuously), Tilt: 0~90°
Pan / Tilt Speed (approximate)	Pan: 0.5~240°/sec., Tilt: 0.5~120°/sec.
Image Masking	-
Aperture Suppress	-
Flickerless	-
Sharpness	-
Built Special Function	-
Network / Remote Control	RS-485
Address / Presets / Protocol	Address: 1024, Preset: 128, Protocol: 18 (BaudRate: 2400~19200bps)
Users	-
Video Resolution & Speed	-
Image Quality	-
Power Supply & Consumption	AC24V
Operation Temperature & Humidity	-10°C ~ +50°C ; RH 95% (max.)
Storage Temperature	-20°C ~ +60°C ; RH 95% (max.)
Dimension (w/o bracket) (approximate)	200(Φ) x 336(h) mm
Weight (w/o bracket) (approximate)	4.5 kg