



VSD-61	
Image Pickup Device	1/4" VZOR Super Colour CCD
Resolution	480 TV Lines
Pixels	752(H) x 582(V)
Lens	27x Optical Zoom (f=3.6~98mm)
Video Output	1.0 Vp-p 75ohm (BNC type)
Audio Output	-
Alarm Input / Output	In: 4ch.
Iris Control	Auto / Manual
Shutter Mode	1/3 ~ 1/10000 sec.
S/N Ratio	≥ 48dB (AGC off)
Gamma Characteristic	-
Scanning System & Frequency	15.625KHz (H) x 50Hz (V)
Gain Control & White Balance	Auto/ Manual/ Interior/ Exterior/ ATW
Backlight Mode	On / Off
Minimum Illumination	0.01 Lux
Day / Night Function	-
IR Sensitive	-
IR LED	-
IR Coverage / Viewing Range (approximate)	-
Pan / Tilt Angle (approximate)	Pan: 360° (continuously), Tilt: 0~90°
Pan / Tilt Speed (approximate)	Pan: 0~80°/sec., Tilt: 0~40°/sec.
Image Masking	-
Aperture Suppress	-
Flickerless	-
Sharpness	-
Built Special Function	Move to specific location when alarm triggered (4 preset positions)
Network / Remote Control	RS-485
Address / Presets / Protocol	Address: 1024, Preset: 64, Protocol: 15 (BaudRate: 2400~19200bps)
Users	-
Video Resolution & Speed	-
Image Quality	-
Power Supply & Consumption	DC15V 1.5A
Operation Temperature & Humidity	0°C ~ +40°C ; RH 95% (max.)
Storage Temperature	-20°C ~ +60°C ; RH 95% (max.)
Dimension (w/o bracket) (approximate)	180(Φ) x 172(h) mm
Weight (w/o bracket) (approximate)	2 kg