



|  | VSD-63   |
|--|--|
| <b>Image Pickup Device</b>                       | 1/4" VZOR Super Colour CCD   |
| <b>Resolution</b>                                | 540 TV Lines   |
| <b>Pixels</b>                                    | 795(H) x 596(V)  |
| <b>Lens</b>                                      | 27x Optical Zoom (f=3.6~98mm)  |
| <b>Video Output</b>                              | 1.0 Vp-p 75ohm (BNC type)  |
| <b>Audio Output</b>                              | -  |
| <b>Alarm Input / Output</b>                      | -  |
| <b>Iris Control</b>                              | Auto / Manual  |
| <b>Shutter Mode</b>                              | 1/3 ~ 1/10000 sec.   |
| <b>S/N Ratio</b>                                 | ≥ 48dB (AGC off)   |
| <b>Gamma Characteristic</b>                      | -  |
| <b>Scanning System &amp; Frequency</b>           | 15.625KHz (H) x 50Hz (V)   |
| <b>Gain Control &amp; White Balance</b>          | Auto/ Manual   |
| <b>Backlight Mode</b>                            | On / Off   |
| <b>Minimum Illumination</b>                      | <b>Colour:</b> 1 Lux, <b>B/W:</b> 0.01 Lux   |
| <b>Day / Night Function</b>                      | Yes  |
| <b>IR Sensitive</b>                              | -  |
| <b>IR LED</b>                                    | -  |
| <b>IR Coverage / Viewing Range (approximate)</b> | -  |
| <b>Pan / Tilt Angle (approximate)</b>            | <b>Pan:</b> 360° (continuously), <b>Tilt:</b> 0~90°                                    |
| <b>Pan / Tilt Speed (approximate)</b>            | <b>Pan:</b> 0~12°/sec., <b>Tilt:</b> 0~15°/sec.  |
| <b>Image Masking</b>                             | -  |
| <b>Aperture Suppress</b>                         | -  |
| <b>Flickerless</b>                               | -  |
| <b>Sharpness</b>                                 | -  |
| <b>Built Special Function</b>                    | Heater + Fan   |
| <b>Network / Remote Control</b>                  | RS-485   |
| <b>Address / Presets / Protocol</b>              | <b>Address:</b> 1024, <b>Preset:</b> 64, <b>Protocol:</b> 18 (BaudRate: 2400~19200bps) |
| <b>Users</b>                                     | -  |
| <b>Video Resolution &amp; Speed</b>              | -  |
| <b>Image Quality</b>                             | -  |
| <b>Power Supply &amp; Consumption</b>            | AC24V 1.7A   |
| <b>Operation Temperature &amp; Humidity</b>      | -10°C ~ +50°C ; RH 95% (max.)  |
| <b>Storage Temperature</b>                       | -20°C ~ +60°C ; RH 95% (max.)  |
| <b>Dimension (w/o bracket) (approximate)</b>     | 234(Φ) x 347(h) mm   |
| <b>Weight (w/o bracket) (approximate)</b>        | 4.5 kg   |

\*\* Design & specification are subject to change without prior notice \*\*