



	VSD-64
<i>Image Pickup Device</i>	1/4" VZOR Colour CCD
<i>Resolution</i>	520 TV Lines
<i>Pixels</i>	752(H) x 582(V)
<i>Lens</i>	10x Optical Zoom (f=3.8~38mm), 10x Digital Zoom
<i>Video Output</i>	1.0 Vp-p 75ohm (BNC type)
<i>Audio Output</i>	-
<i>Alarm Input / Output</i>	-
<i>Iris Control</i>	Auto / Manual
<i>Shutter Mode</i>	1/50 ~ 1/120,000 sec.
<i>S/N Ratio</i>	≥ 46dB (AGC off)
<i>Gamma Characteristic</i>	-
<i>Scanning System & Frequency</i>	15.625KHz (H) x 50Hz (V)
<i>Gain Control & White Balance</i>	White Balance: ATW/ Manual
<i>Backlight Mode</i>	-
<i>Minimum Illumination</i>	1.5 Lux
<i>Day / Night Function</i>	Yes (Auto/ Day/ Night)
<i>IR Sensitive</i>	-
<i>IR LED</i>	-
<i>IR Coverage / Viewing Range (approximate)</i>	-
<i>Pan / Tilt Angle (approximate)</i>	Pan: 360° (continuously), Tilt: 0~90°
<i>Pan / Tilt Speed (approximate)</i>	Pan: 100 ~ 300°/sec., Tilt: 100 ~ 300°/sec.
<i>Image Masking</i>	Area : 4 (adjustable size, 4*colours)
<i>Aperture Suppress</i>	-
<i>Flickerless</i>	-
<i>Sharpness</i>	-
<i>Built Special Function</i>	Display, Camera, Motion Setup, PTZ, Privacy setting, Language, Resume position/function after idle for a certain time
<i>Network / Remote Control</i>	RS-485
<i>Address / Presets / Protocol</i>	Address: 256, Preset: 128, Protocol: 16 (BaudRate: 2400~19200bps)
<i>Users</i>	-
<i>Video Resolution & Speed</i>	-
<i>Image Quality</i>	-
<i>Power Supply & Consumption</i>	DC12V
<i>Operation Temperature & Humidity</i>	-10°C ~ +50°C ; RH 95% (max.)
<i>Storage Temperature</i>	-20°C ~ +60°C ; RH 95% (max.)
<i>Dimension (w/o bracket) (approximate)</i>	190(Φ) x 220(h) mm
<i>Weight (w/o bracket) (approximate)</i>	2 kg