



VSD-71R	
Image Pickup Device	1/4" Sony Colour CCD
Resolution	700 TV Lines
Pixels	537(H) x 597(V)
Lens	23x Optical Zoom
Video Output	1.0 Vp-p 75ohm (BNC type)
Audio Output	-
Alarm Input / Output	-
Iris Control	Auto / Manual
Shutter Mode	Auto/ 1/50 ~ 1/10,000 sec.
S/N Ratio	≥ 48dB (AGC off)
Gamma Characteristic	-
Scanning System & Frequency	15.625KHz (H) x 50Hz (V)
Gain Control & White Balance	Push/ ATW/ Roll/ User/ Indoor/ Fix/ Outdoor/ Hold/ MWB
Backlight Mode	Off/ HLC/ BLC
Minimum Illumination	Colour: 1 Lux, B/W: 0.01 Lux
Day / Night Function	Auto/ Night/ Colour
IR Sensitive	Yes
IR LED	9x Array IR LED
IR Coverage / Viewing Range (approximate)	10~50m
Pan / Tilt Angle (approximate)	Pan: 360° (continuously), Tilt: 0~90°
Pan / Tilt Speed (approximate)	Pan: 300°/sec., Tilt: 180°/sec.
Image Masking	Off/ On (8*Masking Areas)
Aperture Suppress	-
Flickerless	-
Sharpness	0 ~ 15
Built Special Function	OSD, System Info, Address Setting, Motion, Pattern, Camera, Restore System Default
Network / Remote Control	RS-485
Address / Presets / Protocol	Address: 256, Presets: -, Protocol: Pelco-D/P, Multi-protocol (BaudRate: 2400~19200bps)
Users	-
Video Resolution & Speed	-
Image Quality	-
Power Supply & Consumption	DC24V 3A
Operation Temperature & Humidity	-10°C ~ +50°C ; RH 95% (max.)
Storage Temperature	-20°C ~ +60°C ; RH 95% (max.)
Dimension (w/o bracket) (approximate)	220(Φ) x 360(h) mm
Weight (w/o bracket) (approximate)	3.8 kg