



	SSC – N11
<b>Image Pickup Device</b>	1/3" SONY Super HAD II Colour DSP CCD
<b>Resolution</b>	540 TV Lines
<b>Pixels</b>	752(H) x 582(V)
<b>Lens</b>	3 mm
<b>Video Output</b>	1.0 Vp-p 75ohm (BNC type)
<b>Audio Output</b>	-
<b>Alarm Input / Output</b>	-
<b>Iris Control</b>	-
<b>Shutter Mode</b>	-
<b>S/N Ratio</b>	≥ 55dB (AGC off)
<b>Gamma Characteristic</b>	-
<b>Scanning System / Frequency</b>	-
<b>Gain Control / White Balance</b>	On/ Off; ATW
<b>Backlight Mode</b>	On/ Off
<b>Minimum Illumination</b>	0.55x (AGC On; F2.0), 0.3x (Auto On, F2.0)
<b>Day / Night Function</b>	Yes
<b>IR Sensitive</b>	-
<b>IR LED</b>	-
<b>IR Coverage / Viewing Range (approximate)</b>	-
<b>Pan / Tilt Angle (approximate)</b>	Pan : 0~90°, Tilt : 0~90°
<b>Pan / Tilt Speed (approximate)</b>	-
<b>Image Masking</b>	-
<b>Aperture Suppress</b>	-
<b>Flickerless</b>	-
<b>Sharpness</b>	-
<b>Built Special Function</b>	-
<b>Network / Remote Control</b>	-
<b>Presets</b>	-
<b>Users</b>	-
<b>Video Resolution &amp; Speed</b>	-
<b>Image Quality</b>	-
<b>Power Supply &amp; Consumption</b>	DC12V ; 75mA (approx.)
<b>Operation Temperature &amp; Humidity</b>	-10°C ~ +50°C ; RH 80% (max.)
<b>Storage Temperature</b>	-20°C ~ +60°C ; RH 95% (max.)
<b>Dimension (w/o bracket) (approximate)</b>	84(Φ) x 53(h) mm
<b>Weight (w/o bracket) (approximate)</b>	125 g