



Video Booster, Spilter



V - 1001



V - 2004



V - 2006

	V - 1001	V - 2004	V - 2006
<i>Power Supply</i>	AC 220V	AC 220V	AC 220V
<i>Input</i>	Video In*1 (2Vp-p 75Ω) BNC type	Video In*1 (2Vp-p 75Ω) BNC type	i) Video In*1 (2Vp-p 75Ω) BNC type OR ii) Video In*2 (2Vp-p 75Ω) BNC type
<i>Output</i>	Video Out*1 (2Vp-p 75Ω) BNC type	Video Out*4 (2Vp-p 75Ω) BNC type	i) Video Out*6 (2Vp-p 75Ω) BNC type OR ii) Video Out*3 (2Vp-p 75Ω) BNC type
<i>Max. Transmission Length</i>	RG59 => 1000m RG6 => 1500m	-	-
<i>Bandwidth</i>	10 MHz (75Ω) (+1,-3dB)	-	-
<i>Frequency Response</i>	-	10Hz ~ 75MHz (75Ω) ± 0.5dB	10Hz ~ 75MHz(75Ω) ± 0.5dB
<i>Max. Video Gain</i>	13 dB	-	-
<i>Max. High Frequency Gain</i>	18 dB	-	-
<i>Dimension</i>	150(w)* 45(h)* 195(d) mm	150(w)* 45(h)* 195(d) mm	300(w)* 45(h)* 195(d) mm
<i>Weight</i>	1 kg	1.5 kg	2 kg

** Design & specification are subject to change without prior notice **