

Special DVR w/Monitor , Camera



VA – RM04 4 ch. DVR built-in 14" Colour Monitor

System : PAL / NTSC	Audio Stor: 86.4MB / hour
Compress. : MPEG-4	Alarm In. : 4ch. individual switch input
Memory : 1 or 2 Hardisc	Alarm Out.: 4ch individual switch output
Video In. : 4ch. BNC	Serial In. : RS-485
Video Out.: 1ch BNC	Network : RJ-45 10M/100M Ethernet
Frame rate: 25fps (PAL), 30fps(NTSC)	Protocol : TCP/IP, UDP/IP
Audio In. : 2ch. RCA	Net.Mode : ADSL / ISDN / LAN
Audio Out.: 2ch RCA	Power : AC 220V
Video Stor :	Operating : 0°C ~ 40°C
(Quad) : 180~1260MB / hour	Humidity : <= 80% RH (non condensing)
(Each) : 80~900MB / hour	

VLEE – 699BM2 6" B/W Monitor

Picture tube : 6" CRT
Video Input : 2 ch. (DIN)
Resolution : >= 450 TV Line
Power supply : DC 9 ~32V
Power Consumption : < 15W
Weight : 2.1 kg
Operating Temperatur: -20°C ~ +60°C



VLEE – 399ANN Weatherproof B/W Bullet Camera

Image sensor : 1/3" CCD
Pixel : CCIR : 512(H)*582(V) EIA : 500(H)*492(V)
S/N Ratio : >= 48dB
Min. Illumination : 0.1 Lux (F 1.2)
Lens : 2.8 mm
Resolution : 420 TV Lines
Power supply : DC 12V
Electronic shutter : CCIR : 1/50~1/10000 Sec. Auto EIA : 1/60~1/10000 Sec. Auto
Weight : 100 g



VA – R08 8 ch. Stand-Alone DVR

- Multilingual : English / Chinese	Video : (In) 8ch. BNC (1Vp-p) 75ohm	Network : Serial interface RS232, RS485
- User & Administrator password	: (Out) 3ch. : BNC*2, S-Video*1	: Netwk.interface RJ-45 (Ethernet)
- 8 x HDD Bays	: MPEG-4	: TCP/IP, UDP/IP, ADSL
- AC 220V (20W w/o HDD)	: 25fps(PAL), 30fps(NTSC)	: Adjustable speed & image quality
- Dimension: 420(L)*450(W)*90(H) mm	Audio : (In) 8ch. RCA, (Out) 1ch. RCA	
- Weight : 7 kg (w/o HDD)	Alarm : Motion Detect , 8*individual switch inputs, 8*individual relay switch output	

** Design & specification are subject to change without prior notice **