



**Analog HD !  
40 % Higher Resolution  
than normal analog camera**

**Continue using your normal  
RG59 coaxial cable !!**

VAR – 101	
<b>Image Pickup Device</b>	1/2.8" SONY Exmor HD Colour CMOS Sensor
<b>Resolution</b>	1.4 MegaPixel
<b>Pixels</b>	-
<b>Lens</b>	3.6 mm
<b>Video Output</b>	(BNC type)
<b>Audio Output</b>	-
<b>Alarm Input / Output</b>	-
<b>Iris Control</b>	0 ~ 15
<b>Shutter Mode</b>	1/25 ~ 1/50,000
<b>S/N Ratio</b>	-
<b>Gamma Characteristic</b>	-
<b>Scanning System / Frequency</b>	2:1 Interlace; 15.625KHz (H) x 50Hz (V)
<b>Gain Control / White Balance</b>	<b>Expose :</b> D-WDR, Defog, Sense-up, AGC, Brightness <b>White Balance :</b> AWB, ATW, Indoor, Outdoor, AWC-Set, Manual
<b>Backlight Mode</b>	Off, BLC, NSBLC
<b>Minimum Illumination</b>	0.1 Lux (Colour); 0 Lux (LED on)
<b>Day / Night Function</b>	Auto, Colour, B/W
<b>IR Sensitive</b>	Yes
<b>IR LED</b>	24xIR LED (5mm)
<b>IR Coverage / Viewing Range (approximate)</b>	10~15m
<b>Image Masking</b>	4 x Areas
<b>Sharpness</b>	-
<b>Built Special Function</b>	Digital Effect, Motion, PrivacyMasking, Language Setting, Defect Setting, Sharpness, Monitor, Video out Settings
<b>Network / Remote Control</b>	-
<b>Presets</b>	Camera ID : 0~255
<b>Users</b>	-
<b>Video Resolution &amp; Speed</b>	-
<b>Image Quality</b>	-
<b>Power Supply &amp; Consumption</b>	DC12V <= 300mA
<b>Operation Temperature &amp; Humidity</b>	-20°C ~ +50°C ; RH 85% (max.)
<b>Storage Temperature</b>	-20°C ~ +60°C ; RH 85% (max.)
<b>Dimension (w/o bracket) (approximate)</b>	60(Φ) x 175(d) mm
<b>Weight (w/o bracket) (approximate)</b>	300 g