

Continue using your normal
RG59 coaxial cable !!

Analog HD !
Higher Resolution
than normal analog camera



1080P Full HD
resolution !!!

VASD – 201	
Image Pickup Device	1/2.8" SONY Exmor HD Colour CMOS Sensor
Resolution	2.1 MegaPixel
Pixels	1920 (H) * 1080 (V)
Lens	10x Optical Zoom Lens
Video Output	(BNC type)
Audio Output	-
Alarm Input / Output	-
Iris Control	-
Shutter Mode	1/50 ~ 1/100,000
S/N Ratio	-
Gamma Characteristic	-
Scanning System / Frequency	2:1 Interlace; 15.625KHz (H) x 50Hz (V)
Gain Control / White Balance	White Balance : ATW, Hold, Full, Track3/2/1/0
Backlight Mode	-
Minimum Illumination	0.05 Lux(Colour); 0 Lux (LED on)
Day / Night Function	Auto, Colour, B/W
IR Sensitive	Yes
IR LED	7xIR LED
IR Coverage / Viewing Range (approximate)	20 ~ 30m
Image Masking	-
Sharpness	-
Built Special Function	Camera (OSD,D/N,Mirror,Iris,WB,WDR,2DNR), PTZ(Flip,Joystick,Prop,Speed,North,Zero), AutoRun(Preset,Tour,Pattern,LRscanHomeAct), Display, InfraRed Settings
Network / Remote Control	-
Presets/ Tour	1 ~ 255
Protocol	Pelco-D / Pelco-P
Baud Rate	1200 ~ 19200 bps.
Image Quality	-
Power Supply & Consumption	DC12V <= 500mA
Operation Temperature & Humidity	-20°C ~ +50°C ; RH 85% (max.)
Storage Temperature	-20°C ~ +60°C ; RH 85% (max.)
Dimension (approximate)	(Camera) 130(Φ) x 210(d) mm; (Bracket) 82(w)*115(h)*225(d) mm
Weight (w/o bracket) (approximate)	1.9 kg

** Design & specification are subject to change without prior notice **