



**VB - 0 2 / VB - 03**  
(rear view)



Lens not included



**VB - 101** (rear view)

	VB - 02	VB - 03	VB - 101
<b>Image Pickup Device</b>	1/3" VZOR Colour CCD		1/3" SONY SuperHAD Colour CCD
<b>Resolution</b>	430 TV Lines	470 TV Lines	430 TV Lines
<b>Pixels</b>	500(H) x 582(V)	752(H) x 582(V)	500(H) x 582(V)
<b>Lens</b>	-		
<b>Video Output</b>	1.0 Vp-p 75ohm (BNC type)		
<b>Audio Output</b>	-		
<b>Alarm Input / Output</b>	-		
<b>Iris Control</b>	DC / Video Drive (selectable)		
<b>Shutter Mode</b>	1/50 ~ 1/100,000 sec.		
<b>S/N Ratio</b>	≥ 48dB (AGC off)		
<b>Gamma Characteristic</b>	0.45		
<b>Scanning System &amp; Frequency</b>	2:1 Interlace; 15.625KHz (H) x 50Hz (V)		
<b>Gain Control &amp; White Balance</b>	ATW		EE / AI / AGC-H/L
<b>Backlight Mode</b>	On / Off (selectable)		
<b>Minimum Illumination</b>	0.8 Lux (F:1.2)		0.5 Lux (F:2.0)
<b>Day / Night Function</b>	-		
<b>IR Sensitive</b>	-		Yes
<b>IR LED</b>	-		
<b>IR Coverage / Viewing Range (approximate)</b>	-		
<b>Pan / Tilt Angle (approximate)</b>	-		
<b>Pan / Tilt Speed (approximate)</b>	-		
<b>Image Masking</b>	-		
<b>Aperture Suppress</b>	-		
<b>Flickerless</b>	-		On / Off (selectable)
<b>Sharpness</b>	-		
<b>Built Special Function</b>	Mirror effect (On/Off selectable)		-
<b>Network / Remote Control</b>	-		
<b>Presets</b>	-		
<b>Users</b>	-		
<b>Video Resolution &amp; Speed</b>	-		
<b>Image Quality</b>	-		
<b>Power Supply &amp; Consumption</b>	DC12V 150mA		
<b>Operation Temperature &amp; Humidity</b>	-10°C ~ +50°C ; RH 95% (max.)		
<b>Storage Temperature</b>	-20°C ~ +60°C ; RH 95% (max.)		
<b>Dimension (w/o bracket) (approximate)</b>	45(w) x 45(h) x 58(d) mm		40(w) x 41(h) x 57(d) mm
<b>Weight (w/o bracket) (approximate)</b>	140 g		100 g

\*\* Design & specification are subject to change without prior notice \*\*