



Lens not included

| | VB – 05X |
|--|--|
| Image Pickup Device | 1/3" SHARP Colour Super CCD + 12 bit DSP |
| Resolution | 450 TV Lines |
| Pixels | 320K |
| Lens | - |
| Video Output | 1.0 Vp-p 75ohm (BNC type) |
| Audio Output | - |
| Alarm Input / Output | - |
| Iris Control | DC / Video Drive (selectable) |
| Shutter Mode | EE/ AI (selectable), 1/50 ~ 1/100,000 sec. |
| S/N Ratio | ≥ 48dB (AGC off) |
| Gamma Characteristic | 0.45 |
| Scanning System & Frequency | 2:1 Interlace; 15.625KHz (H) x 50Hz (V) |
| Gain Control & White Balance | WB : ATW: On/Off |
| Backlight Mode | On / Off (selectable) |
| Minimum Illumination | 0.5 Lux (F:2.0) |
| Day / Night Function | - |
| IR Sensitive | - |
| IR LED | - |
| IR Coverage / Viewing Range (approximate) | - |
| Pan / Tilt Angle (approximate) | - |
| Pan / Tilt Speed (approximate) | - |
| Image Masking | - |
| Aperture Suppress | - |
| Flickerless | - |
| Sharpness | - |
| Built Special Function | Mirror effect (On/Off selectable) |
| Network / Remote Control | - |
| Presets | - |
| Users | - |
| Video Resolution & Speed | - |
| Image Quality | - |
| Power Supply & Consumption | DC12V 150mA |
| Operation Temperature & Humidity | -10°C ~ +50°C ; RH 95% (max.) |
| Storage Temperature | -20°C ~ +60°C ; RH 95% (max.) |
| Dimension (w/o bracket) (approximate) | 55(w) x 50(h) x 120(d) mm |
| Weight (w/o bracket) (approximate) | 185 g |

** Design & specification are subject to change without prior notice **