



Lens not included

	VB - 071
Image Pickup Device	1/3" SONY Effio-A SuperHAD II Colour CCD
Resolution	800 TV Lines
Pixels	967(H) x 582(V)
Lens	-
Video Output	1.0 Vp-p 75ohm (BNC type)
Audio Output	-
Alarm Input / Output	-
Iris Control	DC / Video Drive (selectable & Adjustable function)
Shutter Mode	Auto : Adjustable AE Level,AGC Max,Sense UP; Manual : Adjustable Shutter Speed, AGC Max; Fix : Adjustable Shutter Speed, AGC Level
S/N Ratio	≥ 45dB
Gamma Characteristic	0.45
Scanning System & Frequency	2:1 Interlace; 15.625KHz (H) x 50Hz (V)
Gain Control & White Balance	AGC : Auto,Manual,Fix, WB : ATW (adjustable)
Backlight Mode	Adjustable AGC,WhiteBalance/ATW,ATR-Ex,DNR,Day/Night,IR,Lens Shad,Defog,FLinkerness,Anti CR
Minimum Illumination	0.01 Lux (F: 1.2)
Day / Night Function	Day, Night, Auto(Adjustable function)
IR Sensitive	Off, On/Auto(Adjustable optimizer)
IR LED	-
IR Coverage / Viewing Range (approximate)	-
Pan / Tilt Angle (approximate)	-
Pan / Tilt Speed (approximate)	-
Image Masking	Area : 1~15, Colour : 8 types, Pos : H ₁ V ₁ ~H ₂ V ₂
Aperture Suppress	-
Flickerless	Off, On, Auto
Sharpness	Off/ Low/ Mid/ High
Built Special Function	OSD, Scene Mode, Picture Adjust, E-Zoom, Privacy Masking,Motion Detect, System Setting, Language Setting, Maintenance
Network / Remote Control	-
Presets	-
Users	-
Video Resolution & Speed	-
Image Quality	-
Power Supply & Consumption	DC12V 100mA
Operation Temperature & Humidity	-10°C ~ +50°C ; RH 95% (max.)
Storage Temperature	-20°C ~ +60°C ; RH 95% (max.)
Dimension (w/o bracket) (approximate)	50(w) x 50(h) x 70(d) mm
Weight (w/o bracket) (approximate)	200 g