



Lens not included

	VB - 302RD	VB - 331
<b>Image Pickup Device</b>	1/3" SONY Super HAD Colour CCD	1/3" VZOR + SONY Colour CCD
<b>Resolution</b>	480 TV Lines	520 TV Lines
<b>Pixels</b>	752(H) x 582(V)	
<b>Lens</b>	-	
<b>Video Output</b>	1.0 Vp-p 75ohm (BNC type)	
<b>Audio Output</b>	-	
<b>Alarm Input / Output</b>	-	
<b>Iris Control</b>	DC / Video Drive (selectable)	
<b>Shutter Mode</b>	EE/ AI (selectable), Auto / Manual : 1/50 ~ 1/100,000 sec.	
<b>S/N Ratio</b>	≥ 48dB (AGC off)	
<b>Gamma Characteristic</b>	0.45	
<b>Scanning System &amp; Frequency</b>	2:1 Interlace; 15.625KHz (H) x 50Hz (V)	
<b>Gain Control &amp; White Balance</b>	AGC : On / Off, WB : ATW	
<b>Backlight Mode</b>	On / Off (selectable)	
<b>Minimum Illumination</b>	0.5 Lux (F2.0)	0.2 Lux (F2.0)
<b>Day / Night Function</b>	-	
<b>IR Sensitive</b>	Yes	
<b>IR LED</b>	-	
<b>IR Coverage / Viewing Range (approximate)</b>	-	
<b>Pan / Tilt Angle (approximate)</b>	-	
<b>Pan / Tilt Speed (approximate)</b>	-	
<b>Image Masking</b>	-	
<b>Aperture Suppress</b>	-	
<b>Flickerless</b>	-	
<b>Sharpness</b>	-	
<b>Built Special Function</b>	Mirror Effect : On/Off	
<b>Network / Remote Control</b>	-	
<b>Presets</b>	-	
<b>Users</b>	-	
<b>Video Resolution &amp; Speed</b>	-	
<b>Image Quality</b>	-	
<b>Power Supply &amp; Consumption</b>	DC12V 250mA	
<b>Operation Temperature &amp; Humidity</b>	-10°C ~ +50°C ; RH 95% (max.)	
<b>Storage Temperature</b>	-20°C ~ +60°C ; RH 95% (max.)	
<b>Dimension (w/o bracket) (approximate)</b>	54(w) x 45(h) x 110(d) mm	
<b>Weight (w/o bracket) (approximate)</b>	300 g	

\*\* Design & specification are subject to change without prior notice \*\*