



VB - 82	
Image Pickup Device	1/3" Sony Double-Scan + Effio-V Colour Chipset
Resolution	800 TV Lines
Pixels	976(H) x 582(V)
Lens	-
Video Output	1.0 Vp-p 75ohm (BNC type)
Audio Output	-
Alarm Input / Output	-
Iris Control	DC / Video Drive (selectable & Adjustable function)
Shutter Mode	Auto : Adjustable AE Level, AGC Max, Sense UP; Manual : Adjustable Shutter Speed, AGC Max; Fix : Adjustable Shutter Speed, AGC Level
S/N Ratio	≥ 45dB
Gamma Characteristic	0.45
Scanning System / Frequency	2:1 Interlace; 15.625KHz (H) x 50Hz (V)
Gain Control / White Balance	AGC : Auto, Manual, Fix, WB : ATW (adjustable)
Backlight Mode	Off, HLC, BLC
Minimum Illumination	0.01 Lux (F: 2.0)
Day / Night Function	Yes
IR Sensitive	-
IR LED	-
IR Coverage / Viewing Range (approximate)	-
Pan / Tilt Angle (approximate)	-
Pan / Tilt Speed (approximate)	-
Image Masking	Yes (15 areas with individual settings)
Aperture Suppress	-
Flickerless	-
Sharpness	-
Built Special Function	Metal Body; OSD, 3D DNR, WDR, CRT/LCD, Mirror
Network / Remote Control	-
Presets	-
Users	-
Video Resolution & Speed	-
Image Quality	-
Power Supply & Consumption	DC12V < 500mA
Operation Temperature & Humidity	-10°C ~ +50°C ; RH 85% (max.)
Storage Temperature	-20°C ~ +60°C ; RH 85% (max.)
Dimension (w/o bracket) (approximate)	40(w) x 40(h) x 70(d) mm
Weight (w/o bracket) (approximate)	200 g

** Design & specification are subject to change without prior notice **