



Lens not included

VB - H01	
Image Pickup Device	1/3" SONY SuperHAD Colour CCD
Resolution	535 TV Lines
Pixels	752(H) x 582(V)
Lens	-
Video Output	1.0 Vp-p 75ohm (BNC type)
Audio Output	-
Alarm Input / Output	-
Iris Control	DC / Video Drive (selectable)
Shutter Mode	AE: AGC(Normal/Max.); AI: DC Level(0~30),AGC(Normal/Max.); Manual: Speed(1/50,1/100,1/250,1/500,1/1K,1/2K,1/4K,1/10K,1/100K), Gain(5dB,13dB,22dB,30dB) ≥ 48dB (AGC off)
S/N Ratio	0.45
Gamma Characteristic	2:1 Interlace; 15.625KHz (H) x 50Hz (V)
Scanning System & Frequency	AGC : Max. / Normal, WB : Auto/Push/Outdoor/Indoor/Fluorescent/Manual(adjustable)
Gain Control & White Balance	Off / Full: Gain(0~255)/ Area: 5x: Contrast(0~15) Colour: 0.8 Lux (F:2.0), B/W: 0.01 Lux (F1.2)
Backlight Mode	Off / On: Sensitivity:0~10
Minimum Illumination	-
Day / Night Function	-
IR Sensitive	-
IR LED	-
IR Coverage / Viewing Range (approximate)	-
Pan / Tilt Angle (approximate)	-
Pan / Tilt Speed (approximate)	-
Image Masking	Area: 8x, Colour: Hold/Red/Green/Blue, Pos: H ₁ V ₁ ~H ₂ V ₂
Aperture Suppress	On /Off
Flickerless	-
Sharpness	Off/ Low/ Mid/ High
Built Special Function	OSD, Mirror effect, High Lum Reversal (1~12), Negative effect, Reset,
Network / Remote Control	-
Presets	-
Users	-
Video Resolution & Speed	-
Image Quality	-
Power Supply & Consumption	DC12V / AC24V
Operation Temperature & Humidity	-10°C ~ +50°C ; RH 95% (max.)
Storage Temperature	-20°C ~ +60°C ; RH 95% (max.)
Dimension (w/o bracket) (approximate)	54(w) x 45(h) x 110(d) mm
Weight (w/o bracket) (approximate)	325 g

** Design & specification are subject to change without prior notice **