



VBU – 411	
<b>Image Pickup Device</b>	1/ 4" SONY SuperHAD Colour CCD
<b>Resolution</b>	420 TV Lines
<b>Pixels</b>	500(H) x 582(V)
<b>Lens</b>	3.6 mm
<b>Video Output</b>	1.0 Vp-p 75ohm (BNC type)
<b>Audio Output</b>	-
<b>Alarm Input / Output</b>	-
<b>Iris Control</b>	A.E.S
<b>Shutter Mode</b>	1/50 ~ 1/100,000 sec.
<b>S/N Ratio</b>	≥ 48dB (AGC off)
<b>Gamma Characteristic</b>	0.45
<b>Scanning System &amp; Frequency</b>	625 Lines, 50 Field/sec.
<b>Gain Control &amp; White Balance</b>	Auto, ATW
<b>Backlight Mode</b>	Open
<b>Minimum Illumination</b>	1 Lux (F:1.2)
<b>Day / Night Function</b>	-
<b>IR Sensitive</b>	-
<b>IR LED</b>	-
<b>IR Coverage / Viewing Range (approximate)</b>	-
<b>Pan / Tilt Angle (approximate)</b>	-
<b>Pan / Tilt Speed (approximate)</b>	-
<b>Image Masking</b>	-
<b>Aperture Suppress</b>	-
<b>Flickerless</b>	-
<b>Sharpness</b>	-
<b>Built Special Function</b>	-
<b>Network / Remote Control</b>	-
<b>Presets</b>	-
<b>Users</b>	-
<b>Video Resolution &amp; Speed</b>	-
<b>Image Quality</b>	-
<b>Power Supply &amp; Consumption</b>	DC12V 110mA
<b>Operation Temperature &amp; Humidity</b>	-10°C ~ +50°C ; RH 95% (max.)
<b>Storage Temperature</b>	-20°C ~ +60°C ; RH 95% (max.)
<b>Dimension (w/o bracket) (approximate)</b>	30(w) x 25(h) x 80(d) mm
<b>Weight (w/o bracket) (approximate)</b>	125 g

\*\* Design & specification are subject to change without prior notice \*\*