



- 1 Ethernet Port
 - 2 Reset Button
 - 3 Audio Input / Output
- 4 Digital Input / Transistor Output
 - 5 DC 12 V Power Input

VCM – 5611		
<i>Image</i>	<i>Device</i>	Micron Progressive Scan CMOS
	<i>Size</i>	1/3"
	<i>Effective Pixel</i>	1280 x 1024
<i>Minimum Illumination</i>	<i>Colour</i>	0.5 Lux at F1.8 (30IRE, max AGC)
	<i>B/W</i>	0.5 Lux at F1.8 (30IRE, max AGC)
	<i>CDS Sensor</i>	Yes
	<i>IR Sensitivity</i>	From 700nm to 1100nm
<i>Lens</i>	<i>Lens & Viewing Angle</i>	f 4.2 mm / F1.8 (75° Horizontal)
<i>Day / Night Function</i>	<i>Mechanical IR Cut</i>	Yes
<i>Synchronization</i>	<i>Sync. System</i>	Internal
<i>Function</i>	<i>Motion Detection</i>	Yes (3 windows)
	<i>Electronic Shutter</i>	1/10~1/2000 sec. (60Hz), 1/10~1/2000 sec (50Hz)
	<i>Flickerless</i>	1/120 sec.(60Hz), 1/100 sec.(50Hz)
	<i>BLC</i>	Yes
	<i>AGC</i>	Auto (User Defined)
	<i>White Balance</i>	Auto/ Indoor1/ Indoor2/ Outdoor1/ Outdoor2/ Hold Current/ Manual
<i>S/N Ratio</i>	<i>S/N Ratio</i>	> 44 dB
<i>Video Compression</i>	<i>Compression</i>	MPEG-4 / MJPEG
	<i>Picture Resolution</i>	SXGA (1280*1024), HD720 (1280*720), VGA (640*480)
	<i>Image Frame Rate</i>	SXGA: 0~8fps, HD720: 0~10fps, VGA: 0~30fps
<i>Audio Input</i>	<i>Compression</i>	8KHz, Mono, PCM
	<i>Audio Line Input</i>	Unbalanced, 1.4Vp-p, 1Vrms, 3.5mm phone socket
<i>Audio Output</i>	<i>Compression</i>	8KHz, Mono, PCM
	<i>Audio Line Output</i>	Unbalanced, 1.4Vp-p, 1Vrms, 3.5mm phone socket
<i>Alarm</i>	<i>Digital Input</i>	1 x Terminal Block
	<i>Relay Output</i>	1 x Terminal Block
<i>External I/O</i>	<i>Reset Button</i>	Factory Default
	<i>LED</i>	System Status
<i>Network</i>	<i>Ethernet</i>	Ethernet (10/100 Base-T), RJ45
	<i>Protocol</i>	TCP, UDP, IP, HTTP, DHCP, PPPoE, RTP, RTSP, FTP, SMTP, DNS, DDNS, NTP, ICMP, IGMP, ARP, 3GPP
<i>Software</i>	<i>Web Browser</i>	I.E. ver6.0 or above
	<i>SDK</i>	SDK-10000
	<i>Security</i>	Password protection : Configured by Administrator
<i>Operating</i>	<i>Temperature</i>	0°C ~ 50°C (32°F ~ 122°F)
<i>Power</i>	<i>Power Requirement</i>	DC 12V ± 10%, 3.3W
	<i>Power On Ethernet (PoE)</i>	DC 12V ± 10%, 4.3W
<i>Physical</i>	<i>Dimension</i>	67(w) x 55(h) x 129.5(d) mm
	<i>Weight</i>	400 g